# AD NUMBER ADC014196 **NEW LIMITATION CHANGE** TO Approved for public release, distribution unlimited **FROM** Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; 31 DEC 1982. Other requests shall be referred to Naval Ocean Research and Development Activity, NSTL Station, MS 39529. **AUTHORITY** ONR ltr, 31 Jan 2006

### AD NUMBER

### ADC014196

### **CLASSIFICATION CHANGES**

TO: unclassified

FROM: confidential

### LIMITATION CHANGES

### TO:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; 31 DEC 1982. Other requests shall be referred to Naval Ocean Research and Development Activity, NSTL Station, MS 39529.

### FROM:

Controlling DoD Organization. Naval Ocean Research and Development Activity, NSTL Station, MS 39529.

### **AUTHORITY**

31 Dec 1982, per document marking; 31 Dec 1982

# FOR FURTHER TRAN TOLL A



ARL-TR-76-37

Copy No. <u>65</u>

SQUARE DEAL EXPLOSIVE SOURCE (SUS)
PROPAGATION MEASUREMENTS (U)

Stephen K. Mitchell (ed.) Aubrey L. Anderson, Nancy R. Bedford Karl C. Focke, Stephen K. Mitchell

APPLIED RESEARCH LABORATORIES
THE UNIVERSITY OF TEXAS AT AUSTIN
POST OFFICE BOX 8029, AUSTIN, TEXAS 78712

19 July 1976

Prepared for:

NAVAL OCEAN RESEARCH AND DEVELOPMENT ACTIVITY NSTL STATION, MS 39529







HATIONAL SECURITY INFORMATION
UNAUTHORIZED DISCLOSURE
BUBLICT TO CHIMINAL SANCTIONS

### CONFIDENTIAL

**Best Available Copy** 

AD NO.

1. REPORT NUMBER 12 GOVT ACCESSION NO.	READ INSTRUCTIONS BEFORE COMPLETING FORM
	RECIPIENT'S CATALOG NUMBER
	[9]
. TITLE (and Subjitle)	STORE OF REPORT & PERIOD COVERE
SQUARE DEAL EXPLOSIVE SOURCE (SUS) PROPAGATION MEASUREMENTS (U).	technical repert
10	ARL-TR-76-37
7. AUTHOR(e)	CONTRACT OF GRANT NUMBER(s)
Stephen K. Mitchell Aubrey L. Anderson, Karl C. Focke, Stephen K Mitchell	9 Nggo14-75-c-9429
Applied Research Laboratories The University of Texas at Austin Austin, TX 78712	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
1. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE
Naval Ocean Research and Development Activity	19 July 1976
NSTL Station MS 39529	13. NUMBER OF PAGES
14. MON-TOPING MENCY NAME & "DDRESS(II different from Controlling Office)	139 15. SECURITY CLASS. (of Inte report)
(12) 11460.	CONFIDENTIAL
	15. DECLASSIFICATION/DOWNGRADING
4	schedule see reverse side
7. DISTRIBUTION STATEMENT (at the abstract entered in Black 20, if different from	m Report)
7. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from	m Report)
	m Report)
S. SUPPLEMENT ARY NOTES  REY WORDS (Einstinue on severes side if necessary and identify by block number)  SQUARE DEAL.	m Report)
S. SUPPLEMENTARY NOTES  REY TORDS (Continue on reverse side if necessary and identity by block number;  SQUARE DEAL- propagation loss	m Report)
S. SUPPLEMENT ARY NOTES  REY WORDS (Einstinue on severes side if necessary and identify by block number)  SQUARE DEAL.	m Report)
3. SUPPLEMENTARY NOTES  REY WORDS (Continue on reverse side II necessary and identify by block number;  SQUARE DEAL,  propagation loss  acoustic propagation	n Report)
S. SUPPLEMENTARY NOTES  REY WORDS (Continue on reverse side if necessary and identity by block number)  SQUARE DEAL- propagation loss acoustic propagation  ABS MACT (Continue on reverse side if necessary and identity by block number)  (U) During the SQUARE DEAL exercise, explosive sour acquired at twelve receiver locations. Approximat 100 nmi to 2000 nmi extent were executed. This repropagation measurements obtained from the ACODAC, and MABS II receivers. These systems had cannidire throughout the water column. Measurements from 18	rce propagation data were ely fifty source events of port deals with acoustic SURVEY, Ambient Noise Buc ctional receivers distribu
SUPPLEMENTARY NOTES  REY WORDS (Continue on reverse side II necessary and identity by block number)  SQUARE DEAL propagation loss acoustic propagation  ARSYRACT (Continue on reverse side II necessary and identity by block number)  (U) During the SQUARE DEAL exercise, explosive sour acquired at twelve receiver locations. Approximat 100 nmi to 2000 nmi extent were executed. This repropagation measurements obtained from the ACODAC, and MABS II receivers. These systems had canidire	rce propagation data were ely fifty source events of port deals with acoustic SURVEY, Ambient Noise Buc ctional receivers distribu

UNCLASSIFIED SECURITY CLASSIFICATION OF 1

FIED OF THIS PAGE (Phon Data Enlared)

SEGURITY CLASSIFICATION OF THIS PAGE(When Date Entered)

15a.

DD 254, 5 Aug 75

CLASSIFIED BY Cont. NOOO14-75-C-0429

SUBJECT TO GDS OF EO 11652

AUTOMATICALLY DOWNGRADED

TWO YEAR INTERVALS

DECLASSIFIED ON DEC 31 1982

#### ACKNOWLEDGEMENTS

(U) Below are listed some of the persons and organizations who contributed to the acquisition and analysis of the data reported here. The planning and execution of the overall exercise involved a far larger group who are mentioned in Refs. 1-4.

#### Planning and Coordination

ARL/UT

G. E. Ellis

L. D. Hampton

### Environmental Data, Navigation

Naval Oceanographic Office

### ACODAC and ANB Operations

Woods Hole Oceanographic Institution

### ACODAC Signal Processing

ARL/UT

J. A. Shooter

S. L. Watkins

Subject to GDS Declassify: 31 Dec. 1982

#### ANB Signal Processing

Naval Research Laboratory

### MABS II Operations and Signal Processing

Naval Underwater Systems Center

### SURVEY Array Operations and Signal Processing

Western Electric Company

#### SUS Deployment

USNS WILKES (T-AGS 33) USNS KINGSPORT (T-AG 164) RFA OLMEDA (A 124)

NTIS	Willia Section 🗆
DDC	544 Rection
UNANNOU!	ng 🗖
KUSTIFICAT	TARE
BY	
BISTRIBUT	INDIANIFAUTA COLOR

îii

(The reverse of this page is blank.)
UNCLASSIFIED

### TABLE OF CONTENTS

				rage
ACKN	WLET	GEME	nts	iii
LIST	OF F	'IGUR	ES	ix
LIST	OF I	'ABLE	es e	xvi:
I.	INI	RODU	CTION	1
	1.	Bac	kground	1
		a.	SQUARE DEAL	1
		b.	Related Reports	3
		c.	Sources, Receivers, Data Processing	5
	2.	Rep	ort Outline	10
	3.	Sur	mary of Propagation Effects	12
		a.	Range, General	12
		b.	Bottom Effects	13
		c.	Source Depth	14
		đ.	Receiver Depth	14
		e.	Frequency	15
	4.	Pre	sentation Formats	15
II.	PHA	SE I	• -	17
	1.	Exe	rcise and Area Description	17
	2.	USN	S WILKES Source Run, Event 2a	17
		a.	ACODAC, Site 1C	21
			(1) Range Dependence	21
			(2) Source Depth Dependence	21
•			(3) Receiver Depth Dependence	25
			(4) Frequency Dependence	25
		<b>b</b> .	ACODAC, Site 2C	28
			(1) Range Dependence	28
			(2) Source Depth Dependence	28
			(3) Receiver Depth Dependence	32
			(4) Frequency Dependence	32
		c.	Comparison of Sites 1C and 2C	32
	3.	Oth	er Source Runs	36

### TABLE OF CONTENTS (Cont'd)

			Page
II.	3.	a. SURVEY Array, Site 1A	36
		b. SURVEY Array, Site 1B	39
III.	PHA	ASE II	43
	1.	Exercise and Area Description	43
	2.	RFA OLMEDA Source Run, Event 14b	43
		a. ACODAC, Site 2C	48
		(1) Range Dependence	48
		(2) Source Depth Dependence	55
		(3) Receiver Depth Dependence	55
		(4) Frequency Dependence	55
		b. ACODAC, Site 2D	57
		(1) Range Dependence	57
		(2) Source Depth Dependence	61
		(3) Receiver Depth Dependence	61
		(4) Frequency Dependence	62
		c. SURVEY Array, Site 2B	62
		(1) Range Dependence	62
		(2) Source Depth Dependence	64
		(3) Frequency Dependence	64
		d. ANB, Site 2BB	64
		(1) Range Dependence	64
		(2) Source Depth Dependence	69
		(3) Receiver Depth Dependence	69
		e. Comparison of Receiver Sites	69
	3.	Aircraft Source Rul, Event 12m	70
		a. SURVEY Array, Site 2b	70
		b. ANB, Site 2BB	73
		c. ACODAC, Site 2D	73
	4.	Aircraft Source Run, Event 12k	73
		a. SURVEY Array, Site 2B	78
		h. ANR. Site 2RB	78

vi

### TABLE OF CONTENTS (Cont'd)

			Take
III.	4.	c. ACODAC, Site 2D	78
IV.	PHA	SE III	85
	1.	Exercise and Area Description	85
	2.	RFA OLMEDA Source Run, Event 22a	85
		a. ACODAC, Site 3D	89
		(1) Range Dependence	89
		(2) Bottom Effects	89
		(3) Source Depth	96
		(4) Receiver Depth	96
		(5) Frequency Dependence	96
		b. ACODAC, Site 1C	101
		(1) Range Dependence	101
		(2) Boundary Effects	101
		(3) Receiver Depth Dependence	107
		(4) Frequency Dependence	107
		c. SURVEY Array, Site 3Z	112
		(1) Range Dependence	112
		(2) Bottom Effects	112
		(3) Source Depth and Frequency Dependence	116
		d. MABS II, Site 3AA	116
		(1) Range Dependence	116
		(2) Source Depth Dependence	122
		(3) Receiver Depth Dependence	122
		(4) Frequency Dependence	122
		(5) Bottom Effects	123
		e. Comparison of Propagation to Sites 3D and 1C	123
		f. Comparison of Propagation to Sites 3D and 3Z	125
v.	COM	PARISON OF REGIONS	127
	1.	Comparison of Phase I and Phase III, Site 10	127
	2.	Comparison of Phase I and Phase II, Site 2C	129
REFER	ence	5	131

vii

(The reverse of this page is blank.)
UNCLASSIFIED

### LIST OF FIGURES

Figure	<u>Title</u>	Page
I-1	SQUARE DEAL EXERCISE AREA AND RECORDING SITES (U)	2
II-1	SUS EVENTS OF PHASE I (U)	18
II-2	SOUND VELOCITY STRUCTURE AND BATHYMETRY IN ROCKALL TROUGH Phase II - Track Along Event 14b	19
II-3	PROPAGATION LOSS - SITE 1C, EVENT 2a 1944 m Receiver Two Source Depths 25, 50, and 158 Hz	22
II-4	PROPAGATION LOSS - SITE 1C, EVENT 2a 712 m, 2860 m Receivers 91 m Source 25, 50, and 158 Hz	23
II-5	RANGE AVERAGED PL versus FREQUENCY - SITE 2C, EVENT 2a 712 m, 1944 m, 2860 m Receivers Two Source Depths	24
II-6	PROPAGATION LOSS DIFFERENCES - SITE 1C Difference Between PL to Receivers Two Source Depths 25 Hz Frequency	26
II-7	PROPAGATION LOSS DIFFERENCES - SITE 1C Three Receiver Depths Two Source Depths Difference Between 158 Hz FL and 50 Hz PL	27
II-8	PROPAGATION LOSS - SITE 2C, EVENT 2a 2066 m Receiver Two Source Depths 25, 50, and 158 Hz	29
II-9	PROPAGATION LOSS - SITE 2C, EVENT 2a 1450 m, 2777 m Receivers 18 m Source Depth 25, 50, and 158 Hz	30
II-10	RANGE AVERAGED PL versus FREQUENCY - SITE 2C, EVENT 2a 1450 m, 2066 m, 2777 m Receivers Two Source Depths	31

## LIST OF FIGURES (Cont'd)

Figure	<u>Title</u>	Page
II-11	PROPAGATION LOSS DIFFERENCES - SITE 2C, EVENT 2a Difference Between PL to Receivers Two Source Depths 50 Hz Frequency	33
II-12	PROPAGATION LOSS DIFFERENCES - SITE 2C, EVENT 2a Three Receiver Depths Two Source Depths Difference Between 158 Hz PL and 50 Hz PL	34
II-13	PROPAGATION LOSS - SITE 1A, EVENT 5a 1802 m Receiver (Bottomed) Two Source Depths 50, 100, and 141 Hz	37
II-14	PROPAGATION LOSS - SITE 1A, EVENT 5f 1802 m Receiver (Bottomed) Two Source Depths 50, 100, and 141 Hz	38
II-15	PROPAGATION LOSS - SITE 1B, EVENT 7b 2038 m Receiver Two Source Depths 50, 141, and 300 Hz	40
II-16	PROPAGATION LOSS - SITE 1B, EVENT 51 2038 m Receiver Two Source Depths 50, 141, and 300 Hz	41
III-l	SUS EVENTS OF PHASE II (U)	44
III-5	SOUND VELOCITY STRUCTURE AND BATHYMETRY IN WEST EUROPEAN BASIN Phase I - Track Along Event 2a	46
III-3	SVP AND BATHYMETRY ALONG TRACK FROM 2BB to JAB	47
III-4	PROPAGATION LOSS - SITE 2C, EVENT 14b 2445 m Receiver Two Source Depths 25, 50, and 158 Hz	49
III-5	PROPAGATION LOSS - SITE 2C, EVENT 14b Six Receiver Depths 18 m Source 25 Hz Frequency	50
III-6a	RANGE AVERAGED PL versus FREQUENCY - SITE 2C, EVENT 14b Sources Southwest of Site 2C 1009 m, 1834 m, 3147 m Receivers Two Source Depths	51

### LIST OF FIGURES (Cont'd)

Figure	<u>Title</u>	Page
III-6b	RANGE AVERAGED PL versus FREQUENCY - SITE 2C, EVENT 14b Sources Northeast of Site 2C 1009 m, 1834 m, 3147 m Receivers Two Source Depths.	52
III-6c	RANGE AVERAGED PL versus FREQUENCY - SITE 2C, EVENT 14b Sources Southwest of Site 2C 398 m, 1376 m, 2445 m Receivers Two Source Depths	53
III-6d	RANGE AVERAGED PL versus FREQUENCY - SITE 2C, EVENT 14b Sources Northeast of Site 2C 398 m, 1376 m, 2445 m Receivers Two Source Depths	54
III-7	PROPAGATION LOSS DIFFERENCES - SITE 2C, EVENT 14b 1009 m and 1834 m deceivers 18 m Source Depth Differences Among PL at 25, 50, and 158 Hz	56
8-111	FROPAGATION LOSS - SITE 2D, EVENT 14b Four Receiver Depths 18 m Source Depth 50 Hz	58
III-9a	RANGE AVERAGED PL versus FREQUENCY - SITE 2D, EVENT 14b 585 m, 1810 m Receivers Two Source Depths	59
III-9b	RANGE AVERAGED PL versus FREQUENCY - SITE 2D, EVENT 14b 715 m, 2467 m Receivers Two Source Depths	60
III-10	PROPAGATION LOSS - SITE 2B, EVENT 14b 1728 m Receiver Two Source Depths 50, 141, and 500 Hz	63
III-lla	PROPAGATION LOSS - SITE 2BB, EVENT 146 300 m Receiver 18 m Source 25, 50, 100, 160, and 256 Hz	65
III-11p	PROPAGATION LOSS - SITE 2BB, EVENT 14b 300 m Receiver 91 m Source 25, 50, 100, 160, and 256 Hz	66

## LIST OF FIGURES (Cont'd)

Figure	Title	Page
III-12a	PROPAGATION LOSS - SITE 2BB, EVENT 14b 610 m Receiver 18 m Source 25, 50, 100, 160, and 256 Hz	67
III-12b	PROPAGATION LOSS - SITE 2BB, EVENT 14b 610 Receiver 91 m Source 25, 50, 100, 160, and 256 Hz	68
III-13	PROPAGATION LOSS - SITE 2B, EVENT 12m 1800 m Receiver Two Source Depths (Each Plot) 50, 141, and 300 Hz	71
III-14	PROPAGATION LOGS - SITE 2B, EVENT 12m 1800 m Receiver Two Source Depths 50, 141, and 300 Hz	72
III <b>-</b> 15	PROPAGATION LOSS - SITE 2BB, EVENT 12m 300 m Receiver Two Source Depths 25, 50, 100, 160, and 256 Hz	74
III-16	PROPAGATION LOSS - SITE 2BB, EVENT 12m 610 m Receiver Two Source Depths 25, 50, 100, and 256 Hz	75
III-17	PROPAGATION LOSS - SITE 2D, EVENT 12m Four Receiver Depths 91 m Source 50 Hz	76
III-18	PROPAGATION LOSS - SITE 2D, EVENT 12m 585 m and 1810 m Receivers 91 m Source 25 Hz _nd 158 Hz	77
111-19	PROPAGACION LOSS - SITE 2B, EVENT 12k 1728 m Receiver Two Source Depths 50, 141, and 500 Hz	79
111-50	PROPAGATION LOSS - SITE 2B, EVTVT 12k 1728 m Receiver Two Source Depths 50, 141, and 500 Hz	80

xii

## LIST OF FIGURES (Cont'd)

Figure	<u>Title</u>	Page
III-27.	PROPAGATION LOSS - SITE 2BB, EVENT 12k 300 m Receiver Two Source Depths 25, 50, 160, and 256 Hz	81
111-55	PROPAGATION LOSS - SITE 2BB, EVENT 12k 610 m Receiver Two Source Depths 25, 50, 100, 160, and 256 Hz	<u>&amp;</u> 2
III-23	PROPAGATION LOSS - SITE 2D, EVENT 12k Four Receiver Depths 91 m Source 50 Hz	83
IV-1	SUG EVENGS OF PHASE III (U)	86
IA-S	SOUND VELOCITY STRUCTURE AND BATHYMETRY IN ICELANDIC BASIN Phase III - Track Along Event 22a	88
IV-3a	PROPAGATION LOSS - SITE 3D, EVENT 22a 1078 m Receiver 18 m Source 25, 50, and 158 Hz	90
IV-3b	PROPAGATION LOSS - SITE 3D, EVENT 220 1078 m Receiver 91 m Source 25, 50, and 158 Hz	91
IV-fr	PROPAGATION LOSS - SITE 3D, EVENT 22a 406 m Receiver 91 m Source 50 Hz and 158 Hz	92
IV-4b	PROPAGATION LOSS - SITE 5D, EVENT 22a 1812 m Receiver 91 m Source 25, 50, and 158 Hz	95
IV-5a	RANGE AVERAGED PL versus FREQUENCY - SITE 3D, EVENT 22a Sources Southwest of Site 3D 406 m, 1078 m, 1812 m Receivers Two Source Depths	94
IV-5b	RANGE AVERAGED PL versus FREQUENCY - SITE 3D, EVENT 22a Sources Northeast of Site 3D 466 m, 1078 m, 1812 m Receivers Two Source Depths	95

xiii

## LIST OF FIGURES (Cont'd)

Figure	<u>Title</u>	Page
IV-6a	PROPAGATION LOSS DIFFERENCES - SITE 3D, EVENT 22a Differences Among PL to Receivers 91 m Source 50 Hz	97
IV-6b	PROPAGATION LOSS DIFFERENCES - SITE 3D, EVENT 22a Differences Among PL to Receivers 91 m Source 200 Hz	98
IV-7a	PROPAGATION LOSS DIFFERENCES - SITE 3D, EVENT 22a 1078 m and 1812 m Receivers 18 m Source Difference Between 158 Hz PL and 50 Hz PL	99
IV-7b	PROPAGATION LOSS DIFFERENCES - SITE 3D, EVENT 22a Three Receivers 91 m Source Difference Between 158 Hz PL and 50 Hz PL	100
IV-8a	PROPAGATION LOSS - SITE 1C, EVENT 22a 606 m Receiver 18 m Source 25, 50, and 158 Hz	102
IV-8b	PROPAGATION LOSS - SITE 1C, EVENT 22a 606 m Receiver 91 m Source 25, 50, and 158 Hz	103
I <b>V-</b> 9a	PROPAGATION LOSS - SITE 1C, EVENT 22a 890 m Receiver 18 m Source 25, 50, and 158 Hz	104
I <b>V-</b> 9b	PROPAGATION LOSS - SITE 1C, EVENT 22a 1960 m Receiver 18 m Source 25, 50, and 158 Hz	105
IV-10	RANGE AVERAGED PL versus FREQUENCY - SITE 1C, EVENT 22a 606 m, 890 m, 1960 m Receivers Two Scurce Depths	1.06
IV-lla	PROPAGATION LOSS DIFFERENCES - SITE 1C, EVENT 22a Difference Among PL to Receivers Two Source Depths 25 Hz	108

### TABLE OF CONTENTS (Cont'd)

Figure	<u>Title</u>	Page
IV-11b	PROPAGATION LOSS DIFFERENCES - SITE 1C, EVENT 22a Difference Among PL to Receivers Two Source Depths 50 Hz	109
IV-llc	PROPAGATION LOSS DIFFERENCES - SITE 1C, EVENT 22a Difference Among PL to Receivers Two Source Depths 200 Hz	110
IV-12	PROPAGATION LOSS DIFFERENCES - SITE 1C, EVENT 22a 890 m Receiver Two Source Depths Difference Among PL at Three Frequencies	111
IV-13	SOUND VELOCITY PROFILE AT SITE 3Z	113
IV-14a	PROPAGATION LOSS - SITE 3Z, EVENT 14b 426 m Receiver 18 m Source 50, 100, and 141 Hz	114
IV-14b	PROPAGATION LOSS - SITE 3Z, EVENT 14b 426 m Receiver 91 m Source 50, 100, and 141 Hz	115
IV-15	SVP AT SITE 3A	11.7
IV-16a	PROPAGATION LOSS - SITE 3AA, EVENT 14b 1454 m Receiver 18 m Source 25, 50, and 160 Hz	118
IV-16b	PROPAGATION LOSS - SITE 3AA, EVENT 14b 1454 m Receiver 91 m Source 25, 50, and 160 Hz	119
IV-17a	PROPAGATION LOSS - SITE 3AA, EVENT 14b 165 m Receiver 91 m Source 25, 50, and 160 Hz	120
IV-17b	PROPAGATION LOSS - SITE 3AA, EVENT 14b 2155 m Receiver 91 m Source 25. 50. and 160 Hz	121

XΥ

(The reverse of this page is blank.)

#### LIST OF TABLES

<u>Table</u>	<u>Title</u>	Page
I-1	SUS Source Levels for ACODAC, ANB, and MABS II Processing	7
I-2	SUS Source Levels for SURVEY Processing	9
I-3	Values To Add to SURVEY Propagation Loss Plots for Conformity to Standard Source Levels (Ref. 14)	11
II-1	Reference Locations for Phase I (U)	20
II-2	Comparison Between Propagation to Site 1C and Site 2C for the Range Interval of 300 nm to 400 nm (U)	35
III-l	Reference Locations for Phase II (U)	45
IV-1	Reference Locations for Phase III (U)	87
IV-2	Comparison of Propagation Loss to ACODACs at Sites 3D and 1C During Event 22a, 200 to 300 nm from Receivers (U)	124
IV-3	Comparison of Propagation Loss to ACODAC at Site 3D and SURVEY Array at Site 3Z During Event 22a. Sources over Site 1C (U)	126
V-1	Range Averaged Propagation Loss at Site 1C from Events 2a and 22a (U)	128
V-2	Range Averaged Propagation Loss at Site 2C from Events 2a and 14b (U)	130

(The reverse of this page is blank.)
UNCLASSIFIED

(This page is UNCLASSIFIED.)

#### I. INTRODUCTION

#### 1. Background

#### a. SQUARE DEAL

- (U) The SQUARE DEAL Exercise was conducted 15 July to 15 September 1973. Involved were research vessels, plus aircraft, for acoustic source deployment and surveillance of surface shipping. The exercise area, and the separate Phases, I, II, and III, of the exercise are indicated in Fig. I-1. More detailed maps are provided in the following chapters dealing with individual phases. The exercise was devoted to acquiring environmental, ambient noise, and acoustic propagation information. The acoustic sources for the propagation measurements included explosives (SUS and SCARF charges), PAR guns, and towed cw sources. This report deals with the acoustic propagation from the explosive SUS charges.
- (U) The SUS data were acquired at approximately 12 receiver locations; some locations were occupied at two separate times. There were approximately 50 SUS source events in which the charges were deployed from ships or aircraft. These source tracks were along great circle arcs of lengths from 100 nm to 2000 rm. The source spacings ranged from 0.25 nm for only two short runs to approximately 5.0 nm for aircraft runs; on the major ship tracks, sources at both 91 m and 18 m uepth were spaced 1.0 nm apart. For each source explosion, receivers at 2 to 6 locations recorded the resulting signal. Many of these recordings have been analyzed to determine the propagation loss in frequency bands, and it is these analyses which are reported here. Most of the recordings are available for additional determinations of propagation loss and for more detailed research on different features of propagation in the area.




FIGURE I-1
SQUARE DEAL EXERCISE AREA AND RECORDING SITES (U)

ARL - UT AS-76-942 SKM - DR 7 - 28 - 76

CONFIDENTIAL

- (U) In accordance with the data analysis planning, propagation loss measurem...s from the SUS recordings have been forwarded to users. This reporting was in the form of computer generated plots and/or digital computer tapes. The scale used most often on the plots was 100 nm/in. abscissa and 10 dB/in. ordinate. Because of the large number of plots which are in this report, the plots included here are reduced in size. The computer retrievable records of propagation loss measurements have been archived and are available to qualified users.
- (U) This report has two primary purposes. First, this report provides a survey of the SUS propagation measurements. Second, this report analyzes those features of acoustic propagation in the SQUARE DEAL area that may be discerned from the SUS data and relates these features where possible to known environmental factors. In regard to the first goal, the data presented here do not exhaust the pool of available plots, but rather serve as a guide to the availability and characteristics of the data for particular receiver sites and source runs. In regard to the second goal, the best assessment of the acoustics of the area cannot be made from the SUS propagation loss measurements alone: there is very little SUS data within 100 to 200 nm of the receivers (see section I.l.c), and the SUS runs with a high density of shots were only along the axes of the three major troughs or basins. The information contained in the reports discussed below is needed to form a more complete picture of the area's acoustics.

#### b. Related Reports

(U) Details of the planning, the objectives, and the participants in the exercise may be found in Ref. 1 (SQUARE DEAL Exercise Plan). A postexercise survey of the data actually acquired, and selection and scheduling for the analysis of some of the recordings is given in Refs. 2 and 3 (Data Analysis Plan). Details of the recording devices and the signal processing systems employed are found in Refs. 1 and 3. A summary of the exercise operation, and some preliminary environmental and acoustic data are given by Ref. 4 (Synopsis Report).

- (U) A quality assessment effort was undertaken to verify the quality of the SUS processing; the results of this study are reported in Ref. 5 (Diagnostic Plan). There, it was determined that, with responsible care, the error introduced in the propagation loss measurement by the playback and analysis of the recorded signals is 1.0 dB or less. It should be noted that Ref. 4 mentioned an uncertainty at that time as to the reliability of the ACODAC processing. Reference 5 concluded that the ACODAC processing was of good quality. In addition to the quality assessment, Ref. 5 provided an analysis of the acoustical properties of the ocean bottom in the vicinity of SITES 1C and 1A (Fig. II-1 of the present report).
- (U) There are several reports dealing with specific aspects of the SQUARE DEAL exercise which were prepared by single organizations, but which had received inputs of processed data from several facilities; this report is one of that series. The cw propagation loss report, Ref. 6, should be read with the present report to obtain a more complete picture of acoustic propagation in the area. The environmental oceanographic measurements are reported and analyzed in Ref. 7, whereas the measurements of ambient noise and noise directionality are analyzed in Ref. 8. A study of the SQUARE DEAL area based on theoretical acoustic propagation models, and a comparison of the models with measured data, is given in Ref. 9. Reference 10 is one report of the British activity during SQUARE DEAL.
- (U) An acoustic survey of the SQUARE DEAL area, based upon contributions from the organizations which analyzed the individual aspects of the environment, the acoustic measurements, and the modeling, is provided by Ref. 11 (Environmental Acoustic Summary).
- (U) The question of the determination of the best source levels to use for the SUS sources arose during the analysis of SQUARE DEAL data. As noted in the following subsection, two sets of source level estimates were used to reduce the data reported in the current report. Reference 12 surveys the problem, which came into focus when a comparatively recently acquired set of measurements of source levels differed significantly from previous

4

(U) estimates. However, as reported in Ref. 13, this disparity has in large part been explained (as far as most of the frequencies considered in the present report are concerned) by the discovery of a 3 dB error in the more recent measurements.

### c. Sources, Receivers, Data Processing

- During each of the three phases of the SQUARE DEAL exercise, propagation loss to various receivers from 1.8 lb SUS explosive sources was measured. The two source depths used are 18 m and 91 m (nominal depth of detonation). These sources were deployed from a ship traveling on a primary source track along the main axis of a trough or basin; additional SUS deployment tracks, radial to one of the receiver sites, were flown by aircraft during each phase.
- (U) Receivers included acoustic data capsules (ACODAC), SURVEY arrays, ambient noise buoys (ANB), and moored acoustic buoy systems (MABS II); specifications for these systems are given in Ref. 3. The location of individual receivers and source tracks are described separately for each phase of the exercise in the respective chapters, and shown in Figs. II-1, III-1, and IV-1. Fig. I-1 shows the locations on a large scale map. The ACODAC receivers were located in the center of troughs or basins, on the primary (ship) source track, with at least 400 m of depth excess at the site (though some hydrophones were below the critical depth). Most of the SURVEY, ANB, and MABS sites were atop or on the slopes of ridges or banks surrounding the croughs and basins, but were usually within 20 nm of the open water where there was depth excess.
- (U) The signal processing of the SUS propagation loss data reported here was performed by several organizations. As a minor, though visible, consequence, there are several plotting formats for the propagation loss data in this report. More detailed descriptions of the data signal processing are found in Ref. 3 (Vol. II, Data Analysis Plan). Some features of the different systems are given below. Except for the SURVEY

- (U) data processed on board the receiving ships, all processing was done in a laboratory using magnetic tape recordings.
- (U) The ACODAC data were processed at the Applied Research Laboratories of The University of Texas at Austin (ARL). The ARL system employs digital conversion of the ACODAC recordings (300 Hz bandwidth), followed by computerized techniques for detection and spectral analysis of the shot signals. The length of the transformed (FFT) signal segment was up to 6.83 sec; the actual shot length was determined by a computer algorithm. If shot lengths exceeded 6.83 sec, successive spectra were accumulated. The amount of energy in frequency bands was determined by summing the power spectra over suitable windows.
- Propagation loss for the ACODAC data was determined in one octave bands at 12.5, 25, and 50 Hz and in one-third octave bands at 12.5, 25, 50, 100, 158, 200, and 250 Hz. The 12.5 Hz band data are of questionable value because of calibration and system bandwidth problems. However, the measurements in all of the above bands are archived. In accordance with the data analysis plan (Ref. 2), plots of propagation loss at 25 Hz (one octave), 50 Hz (one octave), and 158 Hz were prepared and forwarded to users. From that body of plots the data presented in the current report was selected.
- (U) The source levels of the SUS sources which were used to reduce the ACODAC data are those determined by Gaspin and Shuler (Ref. 14); these levels are given here in Table I-1. A discussion of these source levels is given in Refs. 12 and 13, which were mentioned in section I.1.b, above. The source levels of Table I-1 were used to process the ANB and MABS II data also.
- (U) The ANB data were processed at Naval Research Laboratory,
  Washington, D.C. (NRL). The NRL system employs digital conversion of the
  ANB recordings, followed by FFT conversion of the signal in 1.0 sec blocks.
  Upon detection, successive spectrum blocks (the number depending upon signal duration) are accumulated. The ANB data were reduced to propagation loss

(U	)	TABLE	T-1

SUS SOURCE LEVELS FOR ACODAC, ANB, AND MABS II PROCESSING

Frequency	18 m sus	91 m SUS			
One-Third Octave Bands					
25 Hz	60.0 dB	60.7 dB			
50	54.9	55.7			
100	53.7	53.3			
160	50.3	51.5			
250	48.6	49.1			
One Octave Bands					
25 Hz	58.6 dB	59.9 dB			
50	55.8	55.6			

Levels are  $dB//l erg/cm^2/Hz$  at 1 ya. (Ref. 14)

- (U) in one octave bands at 25 and 50 Hz, and one-third octave bands at 100, 160, and 256 Hz. The source levels used for the processing are given in Table I-1.
- (U) The MABS II data were processed by the Naval Underwater Systems Center, New London, Connecticut (NUSC). In this system, the MABS II recordings were reproduced into a bank of analog filters which performed the spectral analysis function; the outputs of the filters were then converted to digital form and the signal energy was determined. The MABS II data were reduced to propagation loss in one octave bands at 25 Hz and 50 Hz and in one-third octave bands at 160 Hz. The source levels used are given in Table I-1.
- (U) Most of the SURVEY data were processed on board the receiving platforms by Western Electric Company, Winston-Salem, North Carolina (WECO); this system operated on-line, as the signals were received. In the WECO system, the signal is played through an analog filter bank, then through analog squaring and integrating circuitry. The outputs of the integrations are recorded on moving-pen strip chart recorders and are also monitored by an onboard computer which measures the signal energy in each analysis band. Some of the SURVEY data were subsequently reprocessed (from analog recordings) and/or reformatted at NRL.
- (U) The frequency bands and the source levels used to analyze the SURVEY data differ from those used for the other systems. On board USNS ALBERT J. MYER (T-ARC 6) the analysis was in one-quarter octave bands at 50, 100, and 141 Hz. On board USNS NEPTUNE (T-ARC 2) the analysis was in one-quarter octave bands at either the same three frequencies, or at 50, 141, and 300 Hz.
- (U) Source levels which were used to reduce the SURVEY array data to propagation loss are given by Table I-2, which is from Table V-4 of Ref. 4. As may be seen, the levels in Table I-2 are lower than those of Table I-1. However, the SURVEY propagation loss plots were made at sea and, except

(U)		TABLE I-2				
	SIIS	SOURCE	LEVELS	FOR	SURVEY	PROCESSING

Frequency	18 m SUS	91 m sus				
One-Third Octave Bands						
50 Hz	53.0 dB	52.1 dB				
100	50.2	49.4				
200	48.8	48.2				

(Table V-4 of Ref. 4)

- (U) for the data from Site 3Z, have not been replotted. On the plots of SURVEY data, a correction factor for the propagation loss is indicated. These factors are given in Table I-3; they equal the difference between the standard levels used for SQUARE DEAL (Ref. 14) and the levels used for the SURVEY propagation loss plots (Refs. 4, 12, 13).
- (U) During the period in which the signal processing was performed, an effort was initiated to verify the accuracy of, and the intercomparability of, the laboratory processing systems at ARL, NRL, NUSC, WHOI, and WECO. A principal component of this work was the processing of the same tape recorded signals at the different facilities. The results of that effort are reported in Ref. 5. In general, the intercomparison showed that the propagation loss measured for tape recorded shots at the different facilities varied by ±1.0 dB or less on a shot-by-shot basis.
- (U) The problem of system overloading was particularly severe on the ACODAC data; to a lesser extent, overloading was a problem in the ANB data. The overloading occurs when the peak level of the incoming signals exceeds the dynamic range of the tape recorder; in the ACODACs, this condition caused the data signal to be momentarily switched off and error tones to be recorded for 1 sec. Overloads obscured most of the ACODAC data out to a range of 150 to 200 nm, and the ANB data out to approximately 100 nm to 200 nm. The problem was more frequent for the 91 m shots than for the 18 m shots. As explained below, detected shots which cause overloads are indicated by a special symbol on plots of propagation loss. A consequence of the overloading problem is that there is no propagation loss data from the ANB or ACODAC systems except from ranges 160 nm or more from the systems.

#### 2. Report Outline

(U) Following this introduction, the three principal phases of the exercise are discussed in separate chapters (II, III, IV). For each phase, an area description and details of the exercise such as receiver locations and source tracks are described first. Then the propagation features observed

(U)

TABLE I-3

VALUES TO ADD TO SURVEY PROPAGATION LOSS PLOTS FOR CONFORMITY TO STANDARD SOURCE LEVELS (Ref. 14)

Frequency	18 m sus	91 m SUS
50 Hz	+2 dB	+4 dB (a)
100	+1+	+4 (a)
141	+3	+3 (b)
300	+3	+3 (b)

- (a) difference between values from Tables I-1 and I-2.
- (b) estimate based upon Ref. 13.

- (U) for the principal (chip) source track are described for each receiver site and these observations are compared between sites. Observations based on other source runs are then described and further intercomparisons are made. Following the description of observations for the individual phases, intercomparisons between Phases I and II, and between Phases I and III are given in chapter V.
- (U) In section I.3, a summary description, based on information from all of the phases, is given for the propagation loss dependence on range, source depth, receiver depth, frequency, topography.

### 3. Summary of Propagation Effects

In the following chapters, attention is given to the dependence of propagation loss on range, bottom interaction, source depth, receiver depth, and frequency. Usually, these effects are interrelated. For one example, the difference between the loss from 18 m and 91 m shots at the same range is usually very frequency dependent. As another example, the dependencies of propagation upon source depth, receiver depth, and frequency may have one typical character for sources detonated in deep water where there is depth excess, but the dependencies change if the sources are deployed in a bottom limited situation.

#### a. Range, General

(U) In this report the term open channel, or deep sound channel, will refer to the situation where there is depth excess at the location of the source and everywhere between the source and receiver (for ACODACs) or almost to the receiver (for SURVEY, MABS, and ANB). As a general rule, approximately 400 m of depth excess is needed for good open channel propagation. The situation where the source is at a position such that there is depth deficiency, or where there is an interval of depth deficiency between the source and receiver, will be referred to as a bottom limited channel.

- (C) Considering that most of the SQUARE DEAL area is in deep water, the open channel propagation is probably the most important propagation mode. In most of the area, the deep, or major, sound channel axis was at a depth of 800 m to 1200 m; also, a shallow sound channel at 100 m to 200 m was found over much of the area. In general, the propagation loss to receivers above critical depth in the open channel situation was characterized by cylindrical spreading. However, sometimes there was so much change in the sound velocity structure along the propagation path (for example, during Phase III in the Icelandic Basin) that the propagation loss was increased in one direction and decreased in the opposite.
- (C) One interesting feature of the SUS propagation loss measurements is that there usually is no strong convergence zone/shadow zone structure evident in the data. Individual propagation loss plots usually show data points to be within ±3 dB of an average trend curve.

### b. Bottom Effects

- (U) For the most part, deviations from the general range dependence of propagation loss described above result from topographic effects.
- features are observed. First, the received signal is generally attenuated at a rate of 0.1 dB/nm to 0.5 dB/nm as the source ship crosses a ridge or shelf. The rate of attenuation depends upon the exact bathymetry and sound velocity structure as well as upon the other acoustic parameters. Second, when the sources are detonated over the crest of a ridge or rise, a local minimum of propagation loss to a distant receiver is observed. That is, within a range interval of perhaps 20 nm, propagation loss can be as much as 10 dB less than loss from sources at the same range in the absence of the bottom effects. This slope enhancement occurs because sound is reflected from the edge of the rise into the deep sound channel.

#### c. Source Depth

- (C) For all phases and source events of SQUARE DEAL, the propagation loss from the 18 m deep sources was greater than the propagation loss from the 91 m sources, and the effect is frequency dependent. From the same range, signals from the 91 m sources are as much as 12 dB stronger than signals from the 18 m sources. Most of the source depth effects can be explained in terms of the Lloyd's Mirror effect, described below.
- (U) There is a high bottom loss over most of the area, so that usually only one or two RR or RSR ray arrivals contribute to the received signals. This condition enables sharp "Lloyd's Mirror" or "pressure release" effects to occur. Interference between closely spaced ray pairs causes the received signal spectra to have a modulation of the form  $\sin(f/f_1)$ , where f is the received frequency and  $f_1$  is determined by the time delay between the ray pairs (Ref. 15). The exact value of  $f_1$  depends upon source depth, receiver depth, and the sound velocity structure. Nominal values for  $f_1$  are 25 Hz for the 91 m sources and 150 Hz for the 18 m sources. Because of the filtering used in processing (one octave at 25 Hz, the one-third octave at other frequencies) the effect upon propagation from the 91 m sources is not striking; however, the 18 m source data clearly show a minimum propagation loss at 158 Hz in most cases.

#### d. Receiver Depth

(C) The sites with a variety of receiver depths were those with ACODAC, MABS II, or ANB receiving systems. There, most of the hydrophones are located within the major sound channel, below the upper sound channel axis and above, or within 100 m of, the critical depth, with exceptions of deeper hydrophones at Site 1C during Phase I and Site 2C during Phase II, and a shallow (165 m) receiver at Site 3AA during Phase III. Among the receivers in the sound channel, there was generally little difference in the observed propagation loss. Nominally, to a receiver near critical depth the propagation loss was no more than 3 dB less than the loss to a receiver

(C) at the deep sound channel axis. Results from the few receivers below critical depth indicate that propagation loss increases rapidly below critical depth. In addition, the signal at these deep receivers seems to be most severely affected by topographic blockage or near-blockage (intervals of no, or very little, depth excess) between the source and receiver. The loss to the shallow receiver at Site 3AA was nominally 3 dB greater than the loss to receivers in the main sound channel. At each site, the same general dependence of propagation loss upon source depth and frequency is observed at all receiver depths.

#### e. Frequency

- (C) The nominal dependence of propagation loss in an open channel situation upon frequency is a function of source depth, as discussed above. From the 91 m sources, the losses at 25, 50, and 100 Hz are usually within ±1 dB of each other; the loss at 200 Hz is approximately 3 dB greater than the loss at 100 Hz.
- observed. When the arrivals contain little bottom reflected energy (because of high bottom loss), the Lloyd's Mirror effect discussed above is dominant, and the greatest loss is at 25 Hz and the minimum loss at 158 Hz may be as much as 10 dB less. When significant bottom reflected energy is present, the Lloyd's Mirror effect is not dominant; this occurs at short (less than 100 nm) ranges and in areas of highly reflecting bottoms. In that case, the loss from the 18 m shots is either frequency independent or increases with frequency.

#### 4. Presentation Formats

(U) In the analysis of propagation to individual sites, several types of data displays are used. First, plots of propagation loss versus range for particular source depths and frequency bands to individual hydrophones give an overall view of propagation to each site (for example, Fig. II-3). For

15

# CONFIDENTIAL

(This page is UNCLASSIFIED.)

(U) these figures, the receiver is at zero range; sources generally south or west of the receiver are at negative ranges, and sources north or east of the receiver are at positive range. Each data point is coded in the following manner to provide a measure of the measurement quality and/or measurement problems:

$$\times$$
 S/N > + 3 dB

$$+$$
 + 3 dB >  $S/N$  > 0 dB

$$\circ$$
 0 dB > S/N > - 3 dB

$$\Delta$$
 - 3 dB > S/N

The triangle symbol is plotted along the base of the plot to indicate that a shot was detected at that range, but the signal in the frequency band was very weak. The "O" symbol is plotted along the top of the plot to indicate that a shot which overloaded the recording system was detected at that range. At short ranges, where all data was overloaded, the data was often not processed and no symbol will appear.

- (U) A second display is that of range averaged propagation loss versus frequency, such as Fig. II-5. This type of display provides a useful summary of the frequency, receiver depth, and source depth dependence of propagation loss in an area. As much as possible, the range intervals over which the averages were made were chosen so that the mean trend of the data changed little over the interval.
- (U) Finally, shot-by-shot differences between the loss at the same frequency to different receivers, or between the loss at different frequencies to the same hydrophone, are plotted versus range as in Figs. II-6 and II-7. These displays serve to show the distribution of frequency and depth dependence.

(This page is UNCLASSIFIED.)

#### II. PHASE I


### 1. Exercise and Area Description

- (U) Phase I of SQUARE DEAL was conducted 1-10 August 1973; the region, the location of the receiver, and the events analyzed here are shown in Fig. II-1. The region is the northwestern portion of the West European Basin, an area partially bounded on three sides by the mid-Atlantic Ridge (composed of the Reykjanes Ridge and the Faraday Seamount Group), the Rockall Bank, and the Porcupine Bank. Throughout this basin there is depth excess, but along the perimeter of the area there is depth deficiency.
- (U) The propagation data were recorded by ACODAC systems at Sites 1C and 2C, and SURVEY arrays at Sites 1A and 1B. Ten explosive source runs were made for propagation studies. USNS WILKES (T-AGS 33) made one SUS run, Event 2a, along the major axis of the basin. The remaining runs were flown by aircraft (see Fig. II-1).
- (U) The sound speed structure within this portion of the West European Basin cannot be described by a single representative sound speed profile; due to the influence of three major water flows, the sound speed profile varies throughout the basin. Figure II-2 illustrates the variation in the structure of the sound speed profiles along the major axis of the basin. Table II-1 gives depths of the hydrophones whose data was processed.

#### 2. USNS WILKES Source Run, Event 2a

(U) The major event during Phase I is the SUS run, Event 2a (Fig. II-1), made by USNS WILKES. Figure II-2 illustrates the variations in the sound speed profile and bathymetry along this track; there is depth excess for the entire run. Throughout the southern half of the run the sound speed

17



CONFIDENTIAL




FIGURE II-2

SOUND VELOCITY STRUCTURE AND BATHYMETRY IN ROCKALL TROUGH

Phase II - Track Along Event 14b

ARL - UT AS-76-680 SKM - DR

(C)

1B

SURVEY

Array

51°49.4'N

29°18.65'W

#### TABLE II-1

# REFERENCE LOCATIONS FOR PHASE I (U) (From Table III-1 of Ref. 4)

HYDROPHONE DEPTHS - meters

Critical Depth, Bottom

TYPE SITE LOCATION m re Profile Features and Bottom ACODAC 10 54°53.3'N 400 m Below Channel Axis 712 28°50.7'W 1944 Critical Depth 2860 190 m Off the Bottom ACODAC 2C 1450 51°29.9'N Deep Sound Channel Axis 19°38.0'W 2066 600 m Below Deep Channel Axis 2777 100 m Above Critical Depth 54°52.14'N SURVEY lA 1802 Array Critical Depth, Bottom 25°18.65'W

2038

(U) profile is characterized by two sound channels; these merge together for the northern half of the run and the profiles have a single sound channel. Data collected by the hydrophones shown in Fig. II-2 have been processed for this run.

#### a. ACODAC, Site 1C

(U) At Site 1C, the processed data were from hydrophones at depths of 712 m, 1944 m, and 2860 m. These depths correspond to 400 m below the channel axis, the critical depth, and 190 m above the bottom, respectively. The 2860 m receiver is much deeper below critical depth than any other receiver in the SQUARE DEAL Exercise. Also, as shown by Fig. II-2, this receiver depth is slightly below the peak of the DeSoto Rise, which will partially block propagation from sources SE of Site 1C.

### (1) Range Dependence

Propagation loss measured at the 1944 m hydrophone is presented in Fig. II-3. Figure II-4 shows the propagation losses from the 91 m sources to the hydrophones at 712 m and 2860 m. Range averaged values of propagation loss are given in Fig. II-5. The data from sources close to the receiver are obscured by system overloading, as indicated by the symbols at the top of the plots of Figs. II-3 and II-4. Beyond 200 nm SE (positive ranges) of the Site 1C, the propagation loss dependence upon range approximates cylindrical spreading. However, the amount of spread in the propagation loss curves, due to convergence zone effects, is greater for the deeper receivers (Fig. II-4). The propagation loss from sources NW of 1C (negative ranges) increases rapidly with range, indicating bottom limited propagation as the track approaches the Reykjanes Ridge.

#### (2) Source Depth Dependence

(C) Comparison of propagation losses from sources detonated at depths of 91 m and 18 m consistently exhibit more loss for the 18 m sources.






FIGURE 11-3
PROPAGATION LOSS - SITE 1C, EVENT 2a
1944 = Receiver
Two Source Depths
25, 50, and 158 Hz

AS-76-849 SEM









FIGURE 11-4
PROPAGATION LOSS - SITE 1C, EVENT 2a
712 m, 2860 m Receivers
91 m Source
25, 50, and 158 Hz

AS-76-850 SKH



UNCLASSIFIED


(C) This may be seen in the range averaged data of Fig. II-5. The difference is greater than 10 dB at the low frequencies and decreases as the frequency increases; at 250 Hz, the difference is less than 3 dB.

### (3) Receiver Depth Dependence

depth is a function of source depth and frequency. This may be seen in the range averaged data of Fig. II-5. The loss to the deepest receiver (2860 m) is approximately 10 dB or more greater than the loss to the other receivers. Comparing the 712 m and 1944 m receivers, the average loss from the 18 m sources is the same at these two depths; from the 91 m sources, there is approximately 3 dB more loss at 1944 m receiver depth. Figure II-6 shows the difference between propagation loss from individual shots to the different receiver depths at 25 Hz.

### (4) Frequency Dependence

- (C) The dependence of propagation loss upon frequency at 1C may be seen in Fig. II-5, and in the plots of differences between propagation loss from individual shots at 158 Hz and 50 Hz, Fig. II-7. From the 91 m sources, the propagation loss increases as frequency increases; there is nominally 4 dB more loss at 158 Hz than at 50 Hz on the two shallower receivers; at the 2860 m receiver, the difference is 8 dB.
- varies with receiver depth and source location. The frequency dependence of propagation from sources in the open channel region SS of Site 1C to the receivers above critical depth (Fig. II-5) is typical of much of SQUARE DEAL. That is, there is maximum loss at 25 Hz, and minimum loss at approximately 158 Hz; there is approximately 8 dB more loss at 25 Hz than 158 Hz. This dependence arises from the Lloyd's Mirror effect, discussed in the introduction whereby, if there are no significant bottom reflected arrivals, interference between closely spaced rays from the shallow




RANGE - nm

FIGURE II-6
PROPAGATION LOSS DIFFERENCES - SITE 1C
Difference Between PL to Receivers
Two Source Depths
25 Hz Frequency

UNCLASSIFIED

AS-76-852 SKM



RANGE - nm
FIGURE II-7
PROPAGATION LOSS DIFFERENCES - SITE 1C
Three Receiver Depths
Two Source Depths
Difference Between 158 Hz PL and 50 Hz PL

AS-76-85 SKM

(C) sources causes the level of the lower frequency components to be reduced. From 18 m sources SE of 1C to the 2860 m receiver, and from NW of Site 1C to all receivers, the Lloyd's Mirror effect is not observed, and propagation loss increases with frequency.

#### b. ACODAC, Site 2C

(U) The hydrophones at Site 2C during Phase I whose outputs have been analyzed are at 1450 m, 2066 n, and 2777 m. These depths are the deep sound channel axis, an intermediate depth, and 100 m above the critical depth, as shown in Fig. II-2.


#### (1) Range Dependence


Propagation losses to the 2066 m depth hydrophone are shown in Fig. II-8; Fig. II-9 shows the propagation loss from the 18 m depth sources to the 1450 m and 2777 m hydrophones. Range averaged values of propagation loss to Site 2C are given in Fig. II-10. The loss from 91 m sources at ranges greater than 150 nm approximates cylindrical spreading. This dependence is also seen for loss from the 18 m sources beyond 150 nm at frequencies above 50 Hz. The loss from the 18 m sources increases at a greater rate below 50 Hz because the Lloyd's Mirror effect is not a dominant factor at close ranges (less than 200 nm) but is at greater ranges (see Fig. II-10); this is probably due to changes in bottom reflectivity along the track.

#### (2) Source Depth Dependence


(C) The dependence of propagation loss upon source depth varies with frequency and source location; this may be seen in Fig. II-10. From sources 200 nm or more NW of Site 1C, the loss from the 18 m sources is greater than the loss from the 91 m sources by 8 to 10 dB at 25 Hz and 0 to 3 dB at 158 Hz and above.

28





AS-76-855 SKM



AS-76-856 SKM

RANGE AVERAGED PL versus FREQUENCY - SITE 2C, EVENT 2a

FIGURE 11-10

1450 m, 2066 m, 2777 m Receivers Two Source Depths

UNCLASSIFIED

### (3) Receiver Depth Dependence

Differences between propagation losses at 50 Hz from individual shots to different hydrophones appear in Fig. II-11; the dependence upon receiver depth is also shown by Fig. II-10. As may be seen, the loss from the 18 m sources shows essentially no trend in the receiver depth dependence. However, the loss from the 91 m sources increases with receiver depth, and the averaged differences show no important frequency dependence; the mean loss from 91 m sources is approximately 4 dB greater at the 2777 m depth than at 1450 m.

### (4) Frequency Dependence

- (C) The frequency dependence of the propagation loss to Site 2C is illustrated by the range averaged data of Fig. II-10, and by the shot-by-shot comparison of Fig. II-12. The frequency dependence of the loss from the 91 m sources is essentially independent of receiver depth or source location; there is approximately 3 dB greater mean loss at 158 Hz than at 50 Hz.
- (C) For the 18 m sources, the frequency dependence varies with source location. From 200 nm and beyond, the Lloyd's Mirror effect, evidenced by the minimum loss at 158 Hz (approximately 5 dB less than the loss at 50 Hz), influences the propagation. The 18 m source data available at shorter ranges (most of these shots overloaded the receivers) have a frequency dependence similar to that of the 91 m sources, with loss increasing with frequency.

#### c. Comparison of Sites 1C and 2C

(C) The sound speed profiles in Fig. II-2 show considerable change in structure between Sites 1C and 2C. There is, however, little difference between propagation to receivers at comparable depths at the two sites.

Table II-2 presents propagation losses observed at Sites 1C and 2C averaged

32





FIGURE 11-11
PROPAGATION LOSS DIFFERENCES - SITE 2C, EVENT 2a
Difference Between PL to Receivers
Two Source Depths
50 Hz Frequency

AS-76-857 SKM



(C)

TABLE II-2

COMPARISON BETWEEN PROPAGATION TO SITE 1C AND SITE 2C FOR THE RANGE INTERVAL OF 300 nm TO 400 nm (U)

PROPAGATION LOSS (dB) 18 m SOURCE RECEIVER 91 m SOURCE DEPTH/SITE 25 Hz 50 Hz 158 Hz 25 Hz 50 Hz 158 Hz 1944 m/1C 2066 m/2C 108 104 100 104 116 101 108 106 100 102 102 114 2860 m/1C 2777 m/2C 106 109 116 118 114 116 105 102 104 114 108 105


- (C) over a range interval of 300 nm through 400 nm; in this interval, the sources are near one site, and propagation is to the other. These data allow comparison between hydrophones at similar depths at the two sites. Remember that the 2860 m depth at Site 1C is far below critical depth, whereas the 2777 m depth is in the sound channel at Site 2C (Fig. II-2).
- (C) Considered as a group, the two receivers at Site 2C and the 1944 m receiver at Site 1C have nearly the same average propagation loss (Table II-2). However, the loss to the 2860 m receiver at Site 1C is consistently the greatest in any column; propagation to that receiver is affected by its distance below critical depth, and probably by the DeSoto rise only 30 nm SE of 1C (Fig. II-2).

#### 3. Other Source Runs

(U) Nine aircraft SUS runs were flown during Phase I. Events 5a and 5f, radial to Site 1A, and Events 5i and 7b, radial to Site 1B, are shown in Fig. II-1. Propagation loss to the SURVEY arrays at the origins of these runs has been computed.

#### a. SURVEY Array, Site 1A

- (C) The receiver at Site 1A is near the bottom above a seamount, at 1802 m depth (slightly above the critical depth); the site is at the NW boundary of the West European Basin (Fig. II-1). Event 5a is a radial run at a bearing of 155° across the deeper part of the Basin; Event 5f is at a bearing of 320°. As may be seen in Fig. II-1, the sources for Event 5f are over shallower water than are those of Event 5a, and propagation to Site 1A is across the NW shoulder of the seamount for Event 5f.
- (C) Propagation loss data for these runs are presented in Figs. II-13 and II-14. As discussed in section I.1.c, the correction factors which are given on the plots of the SURVEY data are needed to have the source levels conform to standard values used for the other systems. For both runs, the






FIGURE II-13

PPOPAGATION LOSS - SITE 1A, EVENT 5a


1802 m Receiver (Bottomed)

Two Source Depths

50, 100, and 141 Hz

AS-76-859 SKM

57







FIGURE II-14
PROPAGATION LOSS - SITE 1A, EVENT Sf
1802 m Receiver (Bottomed)
Two Source Depths
50, 100, and 141 Hz

AS-76-860 SKM

(C) loss from the 18 m shots is approximately 5 dB greater than the loss from the 91 m shots. There is no apparent frequency dependence for the 18 m sources. For the 91 m sources, at the longest ranges of both runs, the greatest loss is at 100 Hz. By comparing Figs. II-13 and II-14, it may be seen that there is greater propagation loss on Event 5f than on 5a. For example, at 200 nm range, the loss on Event 5f is nominally 10 dB greater for the 91 m sources and 6 dB greater for the 18 m sources than the loss on Event 5a. This dependence upon propagation path is what would be expected from the bathymetry of the two paths described in the preceding paragraph.

### b. SURVEY Array, Site 1B

- critical depth on a seamount along the mid-Atlantic Ridge. Event 7b is a radial run at a bearing of 20°. Fig. II-1 shows this run across the Icelandic Basin; not shown is the portion at the end of the run (approximately 700 nm from Site 1B) where the track passes over the edge of the Reykjanes Ridge. Event 5i is a radial run at a bearing of 87° across the West European Basin; at approximately 530 nm, the depth at the source changes from greater than 3000 m to less than 1000 m as the track crosses Porcupine Bank.
- Propagation loss data for these runs are presented in Figs. II-15 and II-16. The range scale of Fig. II-16 differs from that of Figs. II-15, II-14, and II-15; also, the highest frequency shown in Figs. II-15 and II-16 is 500 Hz rather than I41 Hz. The propagation loss curves for the two runs show equivalent levels at the same range, frequency, and source depth. From the 91 m sources, the loss at 50 Hz is approximately the same as the loss at 141 Hz; the loss at 300 Hz is approximately 5 dB more at 400 nm than at the other two frequencies and shows attenuation in addition to spreading loss. From the 18 m sources, the loss at 141 Hz is approximately 3 dB less than the loss at 50 Hz; this 1: consistent with the Lloyd's Mirror effect.







FIGURE 11-15
PROPAGATION LOSS - SITE 1B, EVENT 7b
2038 m Receiver
Two Source Depths
50, 141, and 300 Hz

AS-76-861 SKN

40

UNCLASSIFIED

The second secon






FIGURE 11-16
PROFAGATION LOSS - SITE 1B, EVENT 51
2038 m Receiver
Two Source Depths
50, 141, and 300 Hz

AS-76-862 SKN

(C) Near the end of both runs (675 nm on Event 7b and 575 nm on Event 5i), the loss from the 91 m sources increases approximately 5 dB as the runs pass over shallow water; from these locations, few 18 m shots are detected.

(This page is UNCLASSIFIED.)

#### III. PHASE II

#### 1. Exercise and Area Description

- (U) During Phase II, 15-25 August 1973, SUS sources were deployed by RFA OLMEDA (A 124) on a track along the Rockall Trough and by aircraft along 13 tracks radial to Site 2B. Three of the source runs have been selected for analysis. These three runs, shown in Fig. III-1, are the RFA OLMEDA run along the Rockall Trough, Event 14b, and two of the aircraft runs, Events 12k and 12m.
- (U) Propagation loss to four sites is available for Phase II. The systems at these locations, shown in Fig. III-1, are ACODACS at Sites 2C and 2D, an ANB at Site 2BB, and a SURVEY array at Site 2B. In Table III-1, hydrophone depths are related to sound speed profile features and bottom depth for each receiver site.
- (U) Topography and sound speed structure along the track of the RFA OLMEDA source run are related, in Fig. III-2, to the hydrophone depths at Sites 2C and 2D. To better define the topography and sound velocity structure of the Rockall Trough, Fig. III-3 shows a cross section across the trough from Site 2BB to Site 3AB.

#### 2. RFA OLMEDA Source Run, Event 14b

(U) During Event 14b, the RFA OLMEDA deployed SUS charges while traversing 840 nm along the axis of Rockall Trough and the Porcupine Plain (Figs. III-1 and III-2). The signals were received by ACODACS at Sites 2C and 2D, which are on the source track in deep water in the central part of the trough. Signals from the hydrophones shown in Table III-1 at each ACODAC site were analyzed. These data are used to examine propagation in the Rockall. Trough, discussed below. Also examined are data from a SURVEY array at




FIGURE III -1
SUS EVENTS OF PHASE II (U)

ARL - UT AS-76-599 SKM - DR 5 - 10 - 76

(C)

#### TABLE III-1

# REFERENCE LOCATIONS FOR PHASE II (U) (From Table III-1 of Ref. 4)

RECEIVER DATA TYPE SITE LOCATION HYDROPHONE DEPTHS - meters ACODAC 2C 51°30.1'N 398 250 below upper axis 200 above int. maximum 1009 400 below int. maximum 15 '37.2'W 200 above deep axis 1376 175 below deep axis 1375 above critical depth 1834 635 below deep axis 1085 above critical depth 2445 1250 below deep axis 300 above critical 3147 400 below critical 650 above bottom ACODAC 2D 55°12.2'N 585 410 below upper axis 365 above int. maximum 715 540 below upper axis 13°33.1'W 235 above int. maximum 1810 310 below deep axis 590 above critical 2467 70 below critical 330 above bottom 54°08.78'N SURVEY 2B 1728 on the bottom (480 m below lower axis) Array 13°05.33'W 54°00.8'N ANB 2BB 300 120 below upper axis 555 above bottom 12°56.0'W 610 430 below upper axis 245 above bottom

45




FIGURE III-2

SOUND VELOCITY STRUCTURE AND BATHYMETRY IN WEST EUROPEAN BASIN

Phase I - Track Along Event 2a

ARL - UT AS-76-681 SKM - DR 6-17-76




FIGURE III-3
SVP AND BATHYMETRY ALONG TRACK FROM 2BB TO 3AB


- (U) Site 2B on the sloping rise up to Porcupine Bank (Figs. III-1, III-3) and from an ANB at Site 2BB on the Porcupine Bank.
- By comparing Figs. III-2 and II-2, it may be seen that the propagation path in Event 14b is much more bottom limited than the path in Event 2a (Section II). Also, approximately 160 nm NE of Site 2C, there is an interval over which there is depth deficiency; to the NE of that blockage, there is only 400 m, or less, of depth excess. Approximately 7 nm SW of Site 2C, there is a point at which the depth excess is only 200 m. These variations of bathymetry along Event 14b influence the level of the propagation loss, and also can affect the frequency, source depth, and receiver depth dependences.

#### a. ACODAC, Site 2C

(U) The receiver depths at Site 2C are shown in Table III-1. One hydrophone, at 3147 m, is well below the critical depth. Propagation loss from both source depths to the 2445 m receiver is shown in Fig. III-4; loss from the 18 m source at 25 Hz to all receivers is shown in Fig. III-5. Range averaged propagation loss versus frequency to all receivers is given by Figs. III-6.


#### (1) Range Dependence

Several features of the propagation to this site are illustrated in Figs. III-4 and III-5. Average propagation loss increases regularly with range both NE and SW of Site 2C. From 18 m depth source, the rate of propagation loss increase is greater from sources SW of the site than from sources NE of the site so that, at 300 nm range, the propagation loss is from 5 to 10 dB higher from sources to the SW. This may be related to the shallower upper channel axis depth NE of Site 2C, which would allow better coupling from the shallow sources. The rate of increase of loss with range is more symmetrical for the 91 m source depth. In general, at this site, the rate of increase of loss with range from the



Range - nm
FIGURE III-4
PROPAGATION LOSS - SITE 2C, EVENT 14b
2445 m Receiver
Two Source Depths
25, 50, and 158 Hz

AS-76-864 SKM



Range - nm
FIGURE III-5
PROPAGATION LOSS - SITE 2C, EVENT 14b
Six Receiver Depths
18 m Source

AS-76-865 SKM

25 Hz Frequency
UNCLASSIFIED




FIGURE III-6a

RANGE AVERAGED PL versus FREQUENCY - SITE 2C, EVENT 14b

Sources Southwest of Site 2C 1009 m, 1834 m, 3147 m Receivers Two Source Depths

> AS-76-866 SKM




FIGURE 111-6b

RANGE AVERAGED PL versus FREQUENCY - SITE 2C, EVENT 14b

Sources Northeast of Site 2C 1009 m, 1834 m, 3147 m Receivers Two Source Depths

> AS-76-867 SKM




FIGURE III-6c

RANGE AVERAGED PL versus FREQUENCY - SITT 20, EVENT 14b

Sources Southwest of Site 2C 398 m, 1376 m, 2445 m Receivers Two Source Dopths

AS-76-868 SKM




FIGURE III-6d

RANGE AVERAGED PL versus FREQUENCY - SITE 2C, EVENT 14b

Sources Northeast of Site 2C 398 m, 1376 m, 2445 m Receivers Two Source Depths



AS-76-869 SKM

(C) 13 m sources is greater than from the 91 m sources. This source depth effect is most evident at 25 Hz and least evident at 158 Hz.

#### (2) Source Depth Dependence

(C) Propagation loss averaged over range intervals is shown in Fig. III-6. These show that the loss from the 91 m sources is less than from the 18 m sources. Details of the source depth dependence vary with source location in the following manner. From the SW, there is 8 dB to 10 dB more loss from the 91 m sources at all frequencies, whereas from the NW the mean difference is approximately 5 dB at 158 Hz and 10 dB at 25 Hz.

#### (3) Receiver Depth Dependence

Receiver depth dependence is shown by the data in Figs. III-5 and III-6. The maximum difference between propagation loss to the different receiver depths is 12 dB, and is usually less than 10 dB. To the five shallowest hydrophones (398 m to 2445 m), the variation is generally less than 5 dB. As may be seen from Fig. III-6, the loss to the deepest hydrophone (3147) is generally greater than the loss to the other receivers; this effect is greater at higher frequencies (with less than 1 dB difference among the hydrophone depths at 25 Hz) and for the 91 m sources.

#### (4) Frequency Dependence

depth and range dependence. As shown in Fig. III-6, from the deep sources, the propagation loss increases with frequency. From ranges less than 200 miles, Fig. III-6 shows that, on the average, the loss also increases with frequency for the 18 m sources. For longer ranges, the frequency dependence for the 18 m sources shows the influence of the Lloyd's Mirror effect, with a minimum loss at 158 Hz. This range variable frequency dependence is further illustrated in Fig. III-7, which shows the difference between propagation loss at different frequencies from individual shots.




FIGURE 111-7
PROPAGATION LOSS DIFFERENCES - SITE 2C, EVENT 14b
1009 m and 1834 m Receivers
18 m Source Depth
Differences Among PL at 25, 50, and 158 Hz

UNCLASSIFIED

AS-76-870 SKM


#### b. ACODAC, Site 2D


(U) The data analyzed from Site 2D were from hydrophones at 585 m and 715 m depth, both of which are between the upper sound channel axis and the intermediate maximum; at 1810 m, which is 310 m below the deep sound channel axis; and at 2467 m, just 70 m below critical depth but only 330 m above the bottom. Propagation loss at 50 Hz from the 18 m sources to these receivers is shown in Fig. III-8; range averaged propagation loss versus frequency is shown in Fig. III-9.


#### (1) Range Dependence

- (C) Several features of the propagation to Site 2D are shown by the data in Fig. III-8. The short range data are obscured by overloads; however, there is an obvious asymmetry between the loss from sources NE and SW of the site. This asymmetry is related in the following paragraphs to topography and to the sound speed profile shown in Fig. III-2.
- (C) Consider first propagation from sources SW of the site. As shown in Fig. III-8, propagation at 50 Hz from the 18 m source depth to the deepest (2467 m) receiver exhibits a very rapid increase in loss with range out to about 200 nm, and then a recovery to lower loss at about 250 nm, beyond which the loss increases only gradually with range. Though less pronounced, a similar behavior is suggested by the data for the 1810 m receiver. For these two receiver depths, this same benavior is shown by the data for the 91 m source depth and for frequencies of 25 and 158 Hz. Propagation to these deep receivers is apparently being strongly influenced by buthymetry. As shown in Fig. III-2, SW of the site bottom depth is only about 2800 m out to about 175 nm, and beyond increases to an average value larger than 4000 m for ranges greater than 225 nm. At 150 nm SW of Site 2D, there is no depth excess. This topographic influence west of Site 2D is much less of a factor in propagation to the two shallowest hydrophones, especially to the one in the upper sound channel at 585 m.

CONFIDENTIAL








UNCLASSIFIED

FIGURE III-9a

RANGE AVERAGED PL vs FREQUENCY - SITE 2D, EVENT 14b 585 m, 1810 m Receivers

585 m, 1810 m Receivers Two Source Depths



NORTHEAST OF SITE 2D




FIGURE III-9b

RANGE AVERAGED PL vs FREQUENCY - SITE 2D, EVENT 14b
715 m, 2467 m Receivers
Two Source Depths

AS-76-873 SKM

(C) With sources NE of the site, an even stronger topographic influence is exhibited. As shown in Fig. III-2, the depth becomes gradually shallower NE of Site 2D, reaching 2000 m at 180 nm. The very steep rise up to the 150 m Scotland Shelf depth then occurs over an interval of less than 10 nm. A slope enhancement (reduced loss) of up to 10 dB is shown at 190 nm range for all receiver depths (Fig. III-8). As RFA OLMEDA moves over the shallow Scotland Shelf, a rapid increase of loss with range is observed at all receiver depths at Site 2D. These same general features are exhibited by the data at 25 and 158 Hz and also for the 91 m source depth at all three frequencies.

#### (2) Source Depth Dependence

As was seen at Site 2C, the data at Site 2D indicate a more rapid increase of loss with range from the 18 m sources than from the 91 m sources. Although the loss for the two source depths is of similar magnitude at short ranges, the higher rate of increase with range results in as much as 15 dB higher loss from the 18 m sources at 550 nm range SW. This source depth dependence is further illustrated by the range averaged data shown in Fig. III-9.

#### (3) Receiver Depth Dependence

Receiver depth dependence is also shown by Fig. III-9. As previously described, the deepest (2467 m) hydrophone exhibits a high loss for ranges less than about 250 nm. Beyond 300 nm range, maximum difference between loss to the different receiver depths is on the order of 5 dB with minimum loss being shown by the two hydrophones which were closest in depth to the two sound channel axes (i.e., the hydrophones at 585 m and 1810 m depth).

### (4) Frequency Dependence


dependence of the propagation loss from the shallow sources is markedly different from what is seen in most of SQUARE DEAL. There is a minimum in propagation loss at 25 Hz or 50 Hz for both source depths. That is, the Lloyd's Mirror effect does not dominate propagation from the 18 m sources; this is evidence that bottom reflected components constitute a significant portion of the arriving signals. From the 18 m sources, the loss at 200 Hz is approximately 3 dB higher than the loss at 25 Hz. From the 91 m sources, the 200 Hz loss is 6 to 10 dB higher than the 25 Hz loss.

#### c. SURVEY Array, Site 2B

(U) At this site, near Site 2BB of Fig. III-1, on the sloping side of Porcupine Bank at the edge of Rockall Trough, the hydrophone is on the bottom at 1728 m depth. The RFA OLMEDA source run (Event 14b) is not radial to Site 2B, but passes within 65 nm of this site.

### (1) Range Dependence

In Fig. III-10, propagation loss to Site 2B for Event 14b is shown for source depths of 18 and 91 m at frequencies of 50, 141, and 300 Hz. The loss increases with range much faster from sources SW of Site 2B than it does from sources NE of the site; at 150 nm, the loss from the SW is nominally 10 dB greater than the loss from the NE. This is because the path to Site 2B from sources to the SW is bottom limited across the shoulder of Porcupine Bank, as may be seen in Fig. III-1. To the NE, the source track passes onto the shallow Scotland Shelf at about 200 nm range and propagation loss rapidly increases with further range increase. There is some slope enhancement seen at approximately 230 nm range.



RANGE - nm
FIGURE III-10
PROPAGATION LOSS - SITE 2B, EVENT 14b
1728 m Receiver
Two Source Depths
50, 141, and 300 Hz

AS-76-874 SKM

63

#### (2) Source Depth Dependence

(C) The propagation loss from the 18 m sources is greater than the loss from the 91 m sources, with the difference depending upon source location. From the SW of Site 2B, the difference is approximately 5 to 10 dB, while from the NE the difference is approximately 0 dB at 50 Hz and 3 dB at 141 and 300 Hz.

#### (3) Frequency Dependence

(C) These data exhibit an increase of loss with frequency for both source depths similar to that seen at Site 2D.

#### d. ANB, Site 2BB


(U) This ANB system is located in 855 m of water on the Porcupine Bank (Figs. III-1 and III-3). Hydrophone depths are 500 m and 610 m. The site is at the top of a steeply sloping bottom which rises out of the Rockall Trough (the location of the RFA OIMEDA source run). Water depth at the site is less than the deep sound channel axis depth in the nearby Rockall Trough (Fig. III-3) and is almost as shallow as the intermediate maximum in the sound speed profile.

#### (1) Range Dependence

- (U) Propagation loss for RFA OIMEDA source run to the 300 m receiver is shown in Figs. III-lla and III-llb, and to the 610 m receiver in Figs. III-l2a and III-l2b. The source run is nonradial to Site 2BB and the range of closest approach is 65 nm.
- (C) In agreement with the data from the SURVEY array at Site 2B, the ANB (Site 2BB) data exhibit a much more rapid increase of propagation loss with range for sources SW of the site than for sources NE of the site. From the 18 m sources, the difference is approximately 10 dB at 150 nm


64

## CONFIDENTIAL



RANGE - nm
FIGURE III-11a
PROPAGATION LUSS - SITE 288, EVENT 14b
300 m Receiver
18 m Source
25, 50, 100, 160, and 256 Hz


AS-76-875 SION




91 m Source 25, 5. 100, 160, and 256 Hz

AS-76-876

ist. **UNCLASSIFIED** 





UNCLASSIFIED

- (C) range; overloading obscures the effect for the 91 m sources. At the higher frequencies, slope enhancement, similar to that previously noted for Sites 2B and 2D is evident for sources at a range of about 225 nm NE of the receiver.
- Propagation from sources SW of Site 2BB is partially blocked by Porcupine Bank; the effect of the blockage varies with source and receiver depth, and frequency. From 91 m sources in this region, propagation loss at 25 and 50 Hz to the 300 m receiver is 6 to 10 dB less than the loss to the 600 m receiver (the 300 m data also show much more scatter). At the higher frequencies, there is little difference between the receiver depths. (The 18 m shots are weakly detected from sources in this area.)

#### (2) Source Depth Dependence

(C) At all frequencies, the loss at a given range is greater from the 18 m sources than from the 91 m sources. The low signal-to-noise ratio for the 18 m shots makes the difference difficult to estimate (Figs. II-11 and II-12); nominally, the difference is 10 dB at 50 and 100 Hz, and 6 dB at the other frequencies.

#### (3) Receiver Depth Dependence

Very little receiver depth dependence is shown for sources NE of the site (compare Figs. III-11 and III-12). However, the 600 m receiver depth shows much higher losses than the 300 m receiver depth for sources to the SW, as noted.

#### e. Comparison of Receiver Sites

(C) For the ACODACs at both Sites 2C and 2D, data are available for one hydrophone near 1800 m depth and another near 2450 m depth. The range between Sites 2C and 2D is approximately 3CO nm. From both the 18 m

(C) and 91 m sources located between the two sites, the propagation losses seen at the 1800 m receivers over the 300 nm range interval are essentially the same at both sites. However, to the near 2450 m depth receiver, the loss is about 10 dB greater at Site 2D than at Site 2C for ranges out to 200 nm; the levels are about the same at 300 nm. This is an effect of the topography described above for the deeper receivers at Site 2D (Section III-2b).

#### 3. Aircraft Source Run, Event 12m

(U) This run is radial to Site 2B at a bearing of 282°; the track crosses the RFA OIMEDA (Event 14b) track at a range of about 100 nm from Site 2B (see Fig. III-1). Sources were deployed at ranges out to 450 nm from Site 2B. This track passes over the SW edge of Rockall Bank; approximately 160 nm from Site 2B, depth excess (approximately 2500 m) is lost.

#### a. SURVEY Array, Site 2B

- As shown by Fig. III-13, propagation loss from the 91 m sources increased with range to a measured value at Site 2B of approximately 85 dB at 160 nm. Beyond that range the rate of increase in the propagation loss is greater and the data also shows more scatter. From the 18 m sources, the loss is approximately 3 dB greater than the 91 m loss at ranges less than 160 nm, and 10 dB or more greater (when shots are detectable) at the longer ranges.
- (C) The frequency dependence of these data is shown by Fig. III-14; except in one range interval, propagation loss increases with increasing frequency for both source depths. The exception is the 125 to 300 nm range interval over which the deep source data sometimes show the same loss at 50 and 141 Hz and sometimes show higher loss at 50 Hz (decreasing loss with frequency between 50 and 141 Hz).






FIGURE 111-13


PROPAGATION LOSS - SITE 2B, EVENT 1800 m Receiver Two Source Depths (Each Plot) 50, 141, and 300 Hz





UNCLASSIFIED

AS-76-87 SKM






FIGURE III-14

PROPAGATION LOSS - SITE 2B, EVENT 12m

1800 m Receiver Two Source Depths 50, 141, and 300 Hz

AS-76-880 SKM

#### b. ANB, Site 2BB

As shown by Figs. III-15 and III-16, the shots during Event 12b were poorly detected at this site, especially the 18 m shots. From the 91 m sources, at ranges less than approximately 200 nm, the propagation loss is 95 dB at 100 Hz and less, and 100 dB at 160 and 256 Hz. These values are representative for both receiver depths. Beyond that range the propagation loss increases, say, 3 dB at the lower frequencies and 6 to 10 dB at the higher frequencies. These values for propagation loss are approximately 10 dB greater than those reported for Site 2B (Figs. III-13 and III-14).


#### c. ACODAC, Site 2D

(C) At this site, almost all of the signals from the 18 m sources were not detectable; from the 91 m sources, the signals overloaded the ACODAC out to a range of approximately 200 nm, beyond which depth excess at the source was lost (Figs. III-17 and III-18). The effect of the loss of depth excess is seen at a shorter range on the 2467 m receiver, which is below critical depth (Fig. III-17). The nominal value of 105 dB loss at 200 nm is closer to the 100 dB measured at Site 2BB than to the 90 dB reported at the same range at Site 2B. It is notable that beyond 200 nm the propagation loss in most of the plots of Figs. III-17 and III-18 increases at a nominal rate of 10 dB/100 nm, a much greater increase than was seen at Sites 2B and 2BB. This is probably attributable to there being a longer path across the shallow SW end of Rockall Bank to Site 2D than to Sites 2B and 2BB, as may be seen from Fig. III-1.


#### 4. Aircraft Source Run, Event 12k

(U) This run is radial to Site 2B at a bearing of 5°; sources were deployed out to 550 nm range. Once over Rockall Trough, there is open channel propagation out to 150 nm, beyond which the depth decreases over Rockall Bank (Fig. III-1).

CONFIDENTIAL




74




RANGE - nm
FIGURE III-16
PROPAGATION LOSS - SITE 2BB, EVENT 12m
610 m Receiver
Two Source Depths
25, 50, 100, and 256 Hz

AS-76-882 SKM






#### HYDROPHONE DEPTH 1810 m




# PROPAGATION LOSS -

## HYDROPHONE DEPTH 715 m



## HYDROPHONE DEPTH 2467 m





RANGE - nm


FIGURE III-17
PROPAGATION LOSS - SITE 2D, EVENT 12m
Four Receiver Depths
91 m Source
50 Hz


UNCLASSIFIED

AS-76-883 SKM









RANGE - nm
FIGURE III-18
PROPAGATION LOSS - SITE 2D, EVENT 12m
585 m and 1810 m Receivers
91 m Source
25 Hz and 158 Hz

AS-76-884 SKM

#### a. SURVEY Array, Site 2B

and III-20. The loss along this track is similar to what was shown for Event 12m. For example, from the 91 m sources, propagation loss is approximately 85 dB at 200 nm range, and then, as the sources move into the shallower water, the loss increases to approximately 95 to 100 dB at 400 nm. The loss from the 18 m sources is approximately 5 dB greater than the loss from the 91 m sources at ranges greater than 200 nm (Fig. III-19). For both source depths, the loss increases with frequency (Fig. III-20).

#### b. ANB, Site 2BB

(C) The propagation loss to Site 2BB is shown in Figs. III-21 and III-22. Most of the received signals overloaded the system out to 200 nm for the 300 m receiver or 150 nm for the 610 m receiver. As the sources move across the shallow water, the increase in propagation less is greater at the higher frequencies and from the shallower sources. Many more shots were detected at the 610 m receiver than at the 300 m receiver (because of a higher noise level at 300 m), but propagation loss values at the two receiver depths are approximately equal.

#### c. ACODAC, Site 2D

(C) Essentially no data are available for the 18 m source depth because of low signal-to-noise ratio. Better propagation from the sources at 91 m results in data such as shown in Fig. III-23 for 50 Hz propagation loss to receivers at depths of 585 m, 715 m, 1810 m, and 2467 m. The data in Fig. III-23 illustrate both the range and receiver depth dependence. Out to 200 nm range, loss increases faster with range to the deepest hydrophone (2467 m) so that, at 400 nm range, the loss at 2467 m is about 10 dB higher than that observed at the other three hydrophones. The loss from the 91 m sources is essentially the same at 25 and 50 Hz, and 3 to 5 dB higher at 158 Hz than at 50 Hz.

CONFIDENTIAL






FIGURE III-19
PROPAGATION LOSS - SITE 2B, EVENT 12k
1728 m Receiver
Two Source Depths
50, 141, and 300 Hz



UNCLASSIFIED







FIGURE 111-20

PROPAGATION LOSS - SITE 28, EVENT 12k

1728 m Receiver Two Source Depths 50, 141, and 300 Hz

AS-76-886 SKN



AS-76-857







FIGURE 111-22
PROPAGATION LOSS - SITE 288, EVENT 12k
610 m Receiver
Two Source Depths
25, 50, 100, 160, and 256 Hz


AS-76-888 SIM



•







RANGE - nm FIGURE III-23 PROPAGATION LOSS - SITE 2D, EVENT 12k Four Receiver Depths 91 m Source 50 Hz

> AS-76-889 SKM

## CO IFIDENTIAL

(This page is UNCLASSIFIED.)


#### IV. PHASE III

#### 1. Exercise and Area Description

(U) Phase III of SQUARE DEAL was conducted duri. September 1973. The locations of the receivers and the event discussed here are shown in Fig. IV-1. The Icelandic Basin, the area of Phase III, is bounded to the northwest by Reykjanes Ridge and to the southeast by Rockall Bank. The receivers deployed for Phase III were ACODACs at Sites 1C and 3D, SURVEY arrays at Sites 3A and 3Z, and the MABS II at Site 3AA. Information regarding hydrophone depths, etc., for all processed data is given in Table IV-1. The major source event of this phase was Event 22a during which RFA OLMEDA began at point 3ZZ in the Norwegian Sea, proceeded along the Great Circle through Sites 3D and 1C, and completed the SUS event at point 3F, west of the mid-Atlantic ridge. For a second series of source events, aircraft deployed SUS charges along paths radial to Site 3A, including one path across Rockall Bank.

#### 2. RFA OLMEDA Source Run, Event 22a

along the track whose recordings have been processed are shown in Fig. IV-2, along with the bathymetry and sound velocity structure. The Faeroe-Iceland ridge and the Gibbs Fracture Zone in the mid-Atlantic ridge are two obvious geographic influences upon propagation. The sound velocity structure shows considerable change along the track and is particularly asymmetric about Site 1C. From 200 nm NE of Site 1C to Site 3Z there is an upper sound channel with axis at approximately 100 m depth; there is no depth excess along this same interval.



CONFIDENTIAL

FIGURE IT . 1 SUS EVENTS OF PHASE III (U)

(¢)

#### TABLE IV-1

# REFERENCE LOCATIONS FOR PHASE III (U) (From Table III-1 of Ref. 4)

TYPE	SITE	LOCATION		HYDROPHONE DEPTHS - meters
ACODAC	3D	60°24.9'N 19°04.0'W	406 1078 1812	Near upper sound channel axis Near deep sound channel axis 100 m above critical depth
ACODAC	10	54°52.4'n 28°49.2'w	606 895 1960	250 m below sound channel axis 550 m below sound channel axis 100 m below critical depth
SURVEY	3Z	63°09.83'N 12°00.34'W	426	Bottom, near crest of Faeroe- Iceland Ridge. Sound velocity minimum at bottom.
MABS II	3AA	59°07.7'N 19°14.2'W	165 966 1454 2155	
Survey	3A	59°07.67'N 18°38.85'W		
	322	64°28'N		
	3F	51°05.8'n 33°35.9'w		




FIGURE IV-2 SOUND VELOCITY STRUCTURE AND BATHYMETRY IN ICELANDIC BASIN PHASE III - TRACK ALONG EVENT 220

ARL - UT AS-74-682 SKM - DR 6 - 17 - 74

#### a. ACODAC, Site 3D


(U) The processed hydrophones at Site 3D are at 406 m, near the upper sound channel axis, at 1078 m, near the deep sound channel axis, and at 1812 m approximately 100 m above the critical depth. Figure IV-3 shows propagation to the 1078 m receiver from both 18 m and 91 m sources whereas Fig. IV-4 shows propagation loss from only the 91 m sources to the 406 m and 1812 m receivers. Range averaged propagation loss to the three receiver depths in selected range intervals is shown in Fig. IV-5.


#### (1) Range Dependence

Overloading of the received shots within ±200 nm of Site 3D limits discussion of the range dependence of propagation loss to longer ranges. In the open channel region SW of Site 3D, between 200 nm and 600 nm, the range dependence of propagation loss shows approximately cylindrical spreading at 158 Hz and above. At the lower frequencies, the loss is almost independent of range over this interval. Indeed, Figs. IV-4 and IV-5 show propagation loss to the deep receiver even decreasing slightly with range at the lower frequencies.

#### (2) Bottom Effects

NE of Site 3D, most of the shots cause overloads out to 180 nm, where depth excess is lost across the Faeroe-Iceland Ridge. For shots between that point and Site 3Z, the 1812 m receiver shows 10 to 15 dB increase in loss; an effect of this magnitude is probably masked by overloading at the other hydrophones. When the source shots are near point Site 3Z, the 50 Hz data show a local minimum in propagation loss due to edge enhancement. Starting at 650 nm SW of Site 3D at the western end of the Event 22a source run, the Gibbs Fracture Zone (in the mid-Atlantic Ridge) causes a 10 to 15 dB increase in loss from the 91 m sources as RFA OLAEDA traverses the zone; few of the 18 m shots were detectable in that region. At 700 nm SW of Site 3D, which is beyond the short interval








FIGURE IV-3a

PROPAGATION LOSS - SITE 3D, EVENT 22a

1078 m Receiver


18 m Source

25, 50, and 158 Hz

90

**UNCLASSIFIED** 


AS-76-890 SKM



PROPAGATION LOSS - SITE 3D, EVENT 22a 1078 m Receiver 91 m Source 25, 50, and 158 Hz

AS-76-891 SKM


25, 50, and 158 Hz
91
UNCLASSIFIED



Range - nm
FIGURE IV-4a
PROPAGATION LOSS - SITE 3D. EVENT 22a
496 m Receiver
91 m Source
50 Hz and 158 Hz


AS-76-892 SKM

#### 1812 m Hydrophone



PROPAGATION LOSS - SITE 3D. EVENT 22a 1812 m Receiver 91 m Source 25, 50, and 158 Hz

AS-76-893 SKM






FIGURE IV-Sa

RANGE AVERAGED PL versus FREQUENCY - SITE 30, EVENT 22a

Sources Southwest of Site 3D 406 m, 1078 m, 1812 m Receivers Two Source Depths

AS-76-894 SKM




FIGURE IV-5b

RANGE AVERAGED PL versus FREQUENCY - SITE 3D, EVENT 22a

Sources Northeast of Site 3D

406 m, 1078 m, 1812 m Receivers
Two Source Depths

AS-76-895 SKM

(C) of depth deficiency shown in Fig. IV-2, there is evidence of edge enhancement causing propagation loss to be 5 dB less than the values for sources at nearby ranges at all irequencies.

### (3) Source Depth

(C) The difference between the propagation loss from the two source depths over the open channel is similar to that of the rest of SQUARE DEAL: 5 dB more loss from the 18 m source at 158 Hz and 10 to 12 dB more at 25 Hz and 50 Hz; this difference is shown clearly in Fig. IV-5.

### (4) Receiver Depth

The dependence of propagation loss upon receiver depth at Site 3D is shown in the depth difference plots of Fig. IV-6; in addition, Fig. IV-5 also reveals the receiver depth dependencies. The 406 m and 1078 m receivers are at the two sound channel axes; as may be seen, there is effectively no difference between propagation loss to these receivers from the 91 m shots. (Cable strumming makes the 18 m shots undetectable at the 406 m receiver.) In the open channel regions, the loss from the 91 m sources to the 1812 m receiver is on the average 2 to 3 dB greater than the loss to the shallow receivers. Similar plots indicate that the propagation loss from the 18 m sources is independent of receiver depth.

### (5) Frequency Dependence

- (C) Figure IV-7 gives frequency difference plots comparing 158 Hz and 50 Hz propagation loss on a shot-by-shot basis; Fig. IV-5 shows the frequency dependence on a range averaged basis.
- (C) During most of Event 22a, propagation loss from the 91 m sources increases with increasing frequency; for example, the loss at 158 Hz is nominally 4 dB greater than the loss at 50 Hz.

96




FIGURE IV-6a
PROPAGATION LOSS DIFFERENCES - SITE 3D, EVENT 22a
Differences Among PL to Receivers
91 m Source
50 Hz

UNCLASSIFIED

AS-76-89 SKM

199.5 Hz




FIGURE IV-6b
PROPAGATION LOSS DIFFERENCES - SITE 3D, EVENT 22a
Difference: Among TL to Receivers
St m Source
200 Hz

98

AS-76-897 SKM

### 18 m SOURCE







FIGURE IV-7a
PROPAGATION LOSS DIFFERENCES - SITE 3D, EVENT 22a
1078 m and 1812 m Receivers
18 m Source
Difference Between 158 Hz PL and 50 Hz PL

AS-76-SKM

91 m SOURCE







RANGE - nm
FIGURE IV-7b
PROPAGATION LOSS DIFFERENCES - SITE 3D, EVENT 22a
Three Receivers
91 m Source
Difference Between 158 Hz PL and 50 Hz PL

(C) Propagation loss from the 18 m sources shows the frequency dependence common to most of SQUARE DEAL. In the open channel SW of Site 3D, Figs. IV-5 and IV-7b show the loss generally decreasing with frequency up to 160 Hz, and then increasing with frequency up to 250 Hz. However, in the high attenuation regions over Faeroe-Iceland Rise and Gibbs Fracture Zone, the loss from the 18 m sources is approximately independent of frequency.

### b. ACODAC, Site 1C

(C) The hydrophones processed at Site 1C for Phase III are at depths of 606 m, approximately 200 m below the sound channel axis; 890 m; and 1960 m, approximately 100 m below critical depth. Propagation loss from sources at each of the two source depths to the 606 m receiver is given in Fig. IV-8, whereas Fig. IV-9 shows the loss to the 890 m receiver and 1960 m receiver from 18 m sources only. The range averaged propagation loss data are shown in Fig. IV-10.


### (1) Range Dependence

(C) From sources in the interval 250 nm to 600 nm NE of Site 1C, propagation loss increases at a rate greater than that of cylindrical spreading; this is different from the range dependence seen at Site 3D. For the 91 m sources the propagation loss at 600 nm range is approximately 4 to 6 dB greater than the loss at 300 nm. From the 18 m sources, the loss increases between the same ranges by approximately 5 to 8 dB.

#### (2) Boundary Effects

(C) All of the shots SW of Site 1C cause overloading until the Gibbs Fracture Zone is reached at 200 nm range. Between 200 nm and 300 nm SW, propagation loss increases by at least 15 to 20 dB for all frequencies and source depths. At the opposite end of the Event 22a track, the Faeroe-Iceland Ridge influences propagation in two ways. First, there is loss of

### 18 m Source




Range - nm FIGURE IV -8a PROPAGATION LOSS - SITE 1C, EVENT 22a 606 m Receiver 18 m Source 25, 50, and 158 Hz

AS-76-900 SKM

102


### 91 m Source





Range - pm FIGURE IV-8b PROPAGATION LOSS - SITE 1C, EVENT 22a 606 m Receiver 91 m Source 25, 50, and 158 Hz


AS-76-901 SKM

103












Range - nm FIGURE IV-9a
PROPAGATION LOSS - SITE 1C, EVENT 22a
890 m Receiver 18 m Source 25, 50, and 158 Hz

AS-76-902 SKM

104







Range - nm FIGURE IV-9b PROPAGATION LOSS - SITE 1C, EVENT 22a 1960 m Receiver 18 a Source 25, 50, and 158 Hz

AS-76-903 SIN

#### NORTHEAST OF SITE 1C




FIGURE IV-10

RANGE AVERAGED PL versus FREQUENCY - SITE 1C, EVENT 22a 606 m, 890 m, 1960 m Receivers Two Source Depths

AS-76-904 SKH

(C) depth excess at 600 nm NE of Site 1C, as reflected by the increase in and propagation loss from the 91 m sources of 5 to 6 dB at 25 and 50 Hz.

Second, in the shallow water at 700 nm, near point Site 3Z, approximately 5 dB decrease in propagation loss due to edge enhancement is seen at 25 and 50 Hz for the 91 m sources and at 50 and 158 Hz for the 18 m sources.

### (3) Receiver Depth Dependence

Differences between propagation loss to different receivers at Site 1C are given in Fig. IV-11. In general, in the open channel loss is 4 dB to 5 dB greater to the 1960 m receiver (just below critical depth) than to receivers near the axis from 91 m sources at all frequencies. From the 18 m sources, loss to the deep receiver is 1 to 2 dB greater at 25 Hz and 50 Hz and 4 dB greater at 200 Hz. In the high attenuation region over the Gibbs Fracture Zone, the receiver depth dependencies are diminished.

### (4) Frequency Dependence

- (C) The dependence of propagation loss upon frequency at Site 1C is illustrated by Figs. IV-10 and IV-12. From 91 m sources in the open channel NE of Site 1C, the loss at 50 Hz is 2 to 3 dB less than at 25 Hz or at 158 Hz. However, from the 91 m sources in the high attenuation region over the Gibbs Fracture Zone, there is less loss on a shot-by-shot basis (Fig. IV-12) at 158 Hz, than at 50 Hz or 25 Hz; this is similar to the effect of the Faeroe-Iceland Ridge upon the 91 m sources which was seen at Site 2D.
- (C) From the 18 m sources, the frequency dependence is one of decreasing loss with increasing frequency over the open channel region and also over the high attenuation region above the Gibbs Fracture Zone. For example, propagation loss at 50 Hz is 3 dB greater than the loss at 158 Hz. The change in the near surface velocity structure and loss of critical depth which occurs 600 nm NE of Site 1C does cause a change in the frequency

107


#### UNCLASSIFIED 800 800 600 700 800 700 700 900 900 500 200 500 400 400 400 300 300 300 200 100 200 200 890 N)- PL( 606 H) Ê £ PL(1980 N)- PL( 890 100 100 PL(1980 A)- PL( 806 91 m SOURCE 0 0 0 -200 -100 -100 -200 -100 7 -200 -10 1 -300 10 RANGE - nm FIGURE IV-11a -10 2 - 10 0 800 700 800 700 800 700 009 200 600 500 600 200 300 400 400 400 300 300 200 2002 PLI 890 31- PLI 606 PJ £ E 100 PL(1980 N)- PL( 890 18 m SOURCE # 下 れ の 8 0 8 100 100 O C - 100 - 100 7.180 -10]-100-200 01


PROPAGATION LOSS DIFFERENCE - SCULLING PACE -


AS-76-905 SKM

PROPAGATION LOSS DIFFERENCES - SITE 1C, EVENT 22a Differences Among PL to Receivers

Two Source Depths







PROPAGATION LOSS DIFFERENCES - SITE 1C, EVENT 22a 850 m Receiver Two Source Depths

> AS-76-9 SKM

(C) dependence of the 18 m measurements. Figure IV-12 shows that, beyond 600 nm range, the relative frequency dependence of propagation loss from the 18 m sources is similar to that of the 91 m sources.

### c. SURVEY Array, Site 3Z

- (C) The SURVEY array stop Faeroe-Iceland Ridge is located at Site 3Z, on the bottom, in 426 m of water. An SVP taken over Site 3Z is shown in Fig. IV-13; the 1472 m/sec velocity at the bottom is the minimum velocity of the entire area between Site 3Z and Site 1C. Also, recall that propagation loss to the ACODAC receivers from sources near Site 3Z (detonated at 91 m depth) showed a local minimum due to slope enhancement.
- Propagation loss to Site 3Z is shown in Fig. IV-14. The propagation loss curves generally break into three regions. Northeast of Site 3Z, the loss increases very rapidly due to attenuation over the shallow channel. Southwest of Site 3Z, the channel deepens until depth excess is reached approximately 80 nm SW of the receiver; over this interval, propagation loss is characterized by a combination of attenuation and spreading. Beyond 100 nm SW, the propagation loss curves resemble those from the ACODACs at Sites 3D and 1C.

### (1) Range Dependence

(C) There is an open propagation channel from 100 nm to 900 nm SW of Site 3Z. At 50 Hz and 100 Hz, the loss from the 91 m sources increases at a cylindrical spreading rate or less; between 450 nm and 900 nm there is effectively no change in the loss.

#### (2) Bottom Effects

(C) Propagation loss from sources NE of Site 3Z to Sites 3D and 1C is high due to attenuation across the Faeroe-Iceland Rise. Figure IV-14 shows a similar high attenuation in shots received at Site 3Z from nearby

112

#### SOUND VELOCITY (M/SEC)






FIGURE IV-13
SOUND VELOCITY PROFILE AT SITE 3Z

AS-76-909 SKM



(This page is UNCLASSIFLED.)



CONFIDENTIAL

(C) sources (within, say, ±50 nm). The asymmetry of the bottom depth about Site 3Z is reflected in the propagation measurements. The frequency dependence of the attenuation is similar to that observed at Site 3D. Namely, the attenuation of energy at the lower frequencies across the shallow water is greater than the attenuation at the higher frequencies.

### (3) Source Depth and Frequency Dependence

Propagation from sources NE of Site 3Z, across shallow water, shows no source depth dependence at any of the frequencies studied. Southwest of Site 3Z, going into deeper water, the difference between propagation loss from the two source depths increases until, near 150 nm SW, the loss is approximately 15 dB greater from the 18 m sources at 100 Hz and 141 Hz. Beyond 250 nm the loss from the 18 m sources is approximately 10 dB greater than the loss from the 91 m sources.

### d. MABS II, Site 3AA

(U) Event 22a was nonradial to Site 3AA; the range to the point of closest approach was 53 nm. Figure IV-15 shows the sound velocity profile at Site 3AA. The outputs of the hydrophones shown in Table IV-1 have been processed. Propagation loss from the 18 m and 91 m sources to the 1454 m receiver are shown in Fig. IV-16. Figure IV-17 presents the loss from the 91 m source to the 165 m and 2155 m receivers.

### (1) Range Dependence

(C) The open sound channel extends approximately 600 nm to the SW and 250 nm to the NE from Site 3AA; propagation loss to each receiver is roughly symmetrical about the CPA (closest point of approach) of 53 nm. Away from the CPA, the loss increases rapidly out to approximately 150 nm range at frequencies of 100 Hz and below; this effect is more noticeable for the 13 m sources. Beyond approximately 150 nm, the loss increases by only 3 dB or less out to 600 nm to the SW, where bathymetric effects are seen.




FIGURE IV-15 SVP AT SITE 3A

> ARL - UT AS-76-932 SKM - DR 7 - 27 - 76




FIGURE IV-16a

PROPAGATION LOSS - SITE 3AA, EVENT 14b
1454 m Receiver
18 m Source
25, 50, and 160 Hz

AS-76-912 SION




FIGURE IV-16b
PROPAGATION LOSS - SITE 3AA, EVENT 14b
1454 m Receiver
91 m Source
25, 50, and 160 Hz

AS-76-913 SIDI




FIGURE IV-17m
PROPAGATION LOSS - SITE 3AA, EVENT 14b
165 m Receiver
91 m Source
25, 50, and 160 Hz

AS-76-914 SIM

# CONFIDENTIAL (This page is UNCLASSIFIED.)




FIGURE IV-176 PROPAGATION LOSS - SITE JAA, EVENT 146 2155 m Receiver 91 m Source 25, 50, and 160 Hz

AS-76-915 SEM

121

### (2) Source Depth Dependence

(C) The propagation loss from the 18 m source is, in general, greater than the 91 m source propagation loss. At 25 Hz, the 18 m source exhibits 8 to 12 dB more loss. The difference as a function of frequency decreases to approximately 0 dB as the frequency increases to 250 Hz.

### (3) Receiver Depth Dependence

All of the Site 3AA hydrophones were above critical depth; the propagation loss was less to receivers in the deep sound channel than to the other receivers. The 966 m and the 1454 m receivers showed propagation loss within 0.5 dB of each other. The greatest difference among receiver depths was between loss to these deep sound channel receivers and the 165 m receiver in the shallow sound channel; the loss to the 165 m receiver was up to 3 dB greater.

### (4) Frequency Dependence

- (C) Propagation from the 91 m source to Site 3AA is almost independent of frequency for ranges less than 500 to 400 nm, though the 50 Hz and 100 Hz bands have up to 3 dB less loss than do the other bands. At ranges greater than 400 nm, there is 5 dB less loss at 100 Hz than at 25 Hz; propagation loss then increases above 100 Hz. There is a general increase of 4 dB from the minimum at 100 Hz to the level at 250 Hz.
- Propagation loss from the 18 m source to Site 3AA generally decreases with increasing frequency; the exact nature is range dependent.

  Out to 200 nm range, there is 5 dB more loss at 25 Hz than at 100 Hz; beyond 300 nm, the difference is 10 dB.

### (5) Bottom Effects

- Beyond 250 nm to the NE of Site 3AA, depth excess and the surface duct are lost as the source passes over the Faeroe-Icaland Rise. Slope enhancement from sources in the range interval of 250 to 300 nm was observed. At frequencies of 100 Hz and less there is a 5 to 8 dB decrease in propagation loss from the 18 m source due to the slope enhancement; above 100 Hz there is no clear edge enhancement for the 18 m sources. The effect upon the propagation from the 91 m sources amounts to only 1 or 2 dB at 25 Hz and 50 Hz.
- (C) Beyond the region of slope enhancement, propagation loss increased approximately 10 dR over a 30 nm range.
- of 575 nm. Near this range, the 18 m source is not detected for 30 to 40 nm; at approximately 610 nm, the 18 m source is again detected. The loss from the 18 m source after the recovery is approximately 1 dB greater than before the loss of the signal. Within the range interval of 585 nm to 625 nm the loss from the 91 m source shows a 3 to 5 dB increase; then at a range of approximately 655 nm, loss from the 91 m source is approximately 2 to 3 dB greater than it was before the zone.

#### e. Comparison of Propagation to Sites 3D and 1C

structure between Sites 3D and 1C, as is reflected in a slight difference between propagation to the two sites from sources located between them. The range dependence was described in the discussion of each site. Average values of propagation loss over range intervals of 200 to 300 nm and 400 to 500 nm from each site are presented in Table IV-2. Sources in the closer interval are approximately midway between Sites 1C and 3D while those in the farther interval are approximately over the opposite site. At the 200 to 300 nm range, only the shallowest receivers in the 158 Hz band show

(C) TABLE IV-2

COMPARISON OF PROPAGATION LOSS TO ACODACS AT SITES 3D AND 1C DURING EVENT 22a, 200 TO 300 nm FROM RECEIVERS (U)

(A)	200 to 300 nm Range	or 7		7.50 7
	91 m Sources	25 Hz	50 Hz	158 Hz
	1C, 606 m 3D, 406 m	98 ab -	96 <b>đ</b> B 98	97 dB 100
	1C, 890 m 3D, 1078 m	100 100	99 99	101 101
	1C, 1960 m 3D, 1812 m	102 101	102 101	105 104
	18 m Sources			
	1C, 606 m 3D, 406 m	111	108	103 -
	1C, 890 m 3D, 1078 m	112 113	108 104	104 105
	1C, 1960 m 3D, 1812 m	113 112	108 110	106 104
(B)	400 to 500 nm Range			
	91 m Scurces			
	1C, 606 m 3D, 406 m	102	100 99	102 102
	1C, 890 m 3D, 1078 m	102 100	100 99	103 103
	1C, 1960 m 3D, 1812 m	105 102	104 102	107 105
	18 m Sources			
	1C, 606 m 3D, 406 m	11 <sup>1</sup> 4	112 -	108
	1C, 890 m 3D, 1078 m	116 114	112 110	108 107
	1C, 1960 m 3D, 1812 m	117 114	11 <sup>1</sup> 4 112	111 101
		no.l.		

(C) as much as 3 dB difference between sites. At the 400 nm to 500 nm range, the loss from the 91 m sources is 2 to 3 dB greater to Site 1C than to Site 3D on the middle and deepest receivers. This larger difference for the deeper receivers may be partially due to the fact that the 1960 m hydrophone at Site 1C is 100 m below critical depth while the 1812 m hydrophone at Site 3D is 100 m above critical depth.

### f. Comparison of Propagation to Sites 3D and 3Z

(C) At Sites 3D and 3Z, propagation from sources at long ranges (greater than 200 nm, say) is characterized by little dependence upon range at 100 Hz and below. Propagation to Sites 3D and 3Z from sources approximately over Site 1C is compared in Table IV-3. For the column headed 150 Hz, 158 Hz is used at Site 3D and 141 Hz at Site 3Z. The range to Site 3D is approximately 450 nm and to Site 3Z, approximately 700 nm. As may be seen, propagation from the 91 m sources to the one receiver at Site 3Z is equivalent to or better than propagation to the two receivers chosen for comparison at Site 3D; in contrast, propagation from the 18 m sources is better to Site 3D than to Site 3Z.

(C)

### TABLE IV-3

# COMPARISON OF PROPAGATION LOSS TO ACODAC AT SITE 3D AND SURVEY ARRAY AT SITE 3Z DURING EVENT 22a SOURCES OVER SITE 1C (U)

	25 Hz	50 Hz	100 Hz	150 Hz
91 m Sources				
3D, 1078 m	100	99	100	103
3Z (bottom)	-	98	100	102
3D, 1812 m	101	102	103	105
18 m Sources				
3D, 1078 m	114	110	109	107
3Z (bottom)	-	-	111	113
3D, 1812 m	114	112	110	107

#### V. COMPARISON OF REGIONS

#### 1. Comparison of Phase I and Phase III, Site 1C

- and Event 22a of Phase III; Event 2a is a SUS run along the axis of the West European Basin (Fig. II-1) and Event 22a is along the Icelandic Basin (Fig. IV-1). The relative propagation loss from sources in the two basins to Site 1C depends upon source depth, receiver depth, and frequency. Whenever significant differences in the loss from equivalent ranges were observed, there was greater loss from the Icelandic Basin.
- Table V-1 compares range averaged values of propagation loss to receivers near the sound channel axis (712 m for Phase I, 606 m for Phase III) and near critical depth (1444 m for Phase I, 1960 m for Phase III) for two range intervals. There is an open channel for propagation to Site 1C from sources in all four source locations. To receivers at the axis at Site 1C, the mean loss from the 91 m sources in both basins is almost identical. However, to the deeper receivers, the loss from 91 m sources is nominally 2 dB greater for sources in the Icelandic Basin (Event 22a). These comparisons were noted for both range intervals.
- (C) For the 18 m sources the comparison seems to depend upon the range interval. In the 300 to 400 nm interval, the loss from the 18 m sources to hydrophones at the axis are the same from both directions. To the deeper hydrophones, there is approximately 2 dB more loss from sources in the Icelandic Basin. In the 500 to 600 nm interval, the loss from 18 m sources in Event 22a is greater for both receiver depths.

RANGE AVERAGED PROPAGATION LOSS AT SITE 1C FROM EVENTS 2a AND 22a (U) TABLE V-1

		•		•	
Range	250 Hz	114	115	111	511 711
Propagation Loss in the Range Interval 500 to 600 nm	158 Hz	108	109.6	105 104	108
Propagation Loss in the Interval 500 to 600 nm	50 Hz	117	111	101	103
Propaga Interva	25 Hz	115	116	102 102	104
e Range	250 Hz	108 110	107 112	105 106	106
Propagation Loss in the Range Interval 300 to 400 nm	158 Hz	105 106	105 108	101	103
tion Los 1 300 te	50 Hz	109	108	66	99
Propaga Interva	25 Hz	114	115 115	100	101
SOURCE	DEPTH	18		91	
RECEIVER	DEPTH	712 606	1944 1960	712 606	1944 1960
EVENT	NUMBER	2a 22a	2a 22a	2a 22a	228 228

(၁)

#### CONFIDENTIAL

#### 2. Comparison of Phase I and Phase II, Site 20

- Event 14b of Phase II. Event 2a was along the major axis of the West European Basin (Fig. II-1). In the range interval of 200 to 300 nm west of Site 2C the sound speed profile changed from one with a double minimum to one with a single minimum. There was a depth excess along the entire source track. Event 14b was down the Rockall Trough (Fig. III-1). The sound speed profiles along this source track were characterized by a double minimum. At a range of approximately 200 nm NE of Site 2C there was a loss of depth excess for a short range interval (Fig. III-2).
- (C) Table V-2 presents range averaged propagation loss for selected receivers at Site 2C for Events 2a and 14b. For both range intervals, the 91 m source propagation loss was 1 to 2 dB more from the West European Basin than from the Rockall Trough. From the 18 m sources at low frequencies (25 Hz and 50 Hz), there was as much as 3 dB more loss to the SW (Event 2a) than to the NE (Event 14b). At the higher frequencies for the 18 m source, however, there was 1 to 2 dB more loss from the NE than from the SW. This behavi r for the 18 m sources is due to the fact that the Lloyd's Mirror effect was prominent during Event 2a, but was much less rignificant during Event 14b.

### CONFIDENTIAL

RANGE AVERAGED PROPAGATION LOSS AT SITE 2C FROM EVENTS 28 AND 14b (U) TABLE V-2

EVENT	RECEIVER	SOURCI	Propagation	Propag Interv	_ Q	Loss in to 300	the Range	age Jee	T. II	opagat: terval	Propagation Loss in Interval 300 to 400	is in the	e Range	
NUMBER	DEPTH	DEPTH	25 Hz	50 Hz	И	158 Hz	200 Hz	250 Hz	25 Hz	50 Hz	100 胚	158 H	200 Hz	250 服
64 E	1450	1.8	111	106	105	102	104	104	115	108	901	104	105	107
C+T	0) CT		27	COT	QOT	† 101	† 1	T02	777	907	J.O.T	104	1 3	102
ଷ୍ଟ୍ର	2111		111	105	105	102	104	105	114	108	106	105	901	108
14b	2445		110	104	901	50T	106	107	114	107	110	108	108	109
성.	1450	91	86	87	8	100	101	102	100	8	8	100	102	104
140	1376		97	96	26	86	100	100	26	8	100	102	102	103
ଷ	2777		100	102	103	103	104	105	102	104	104	105	901	102
14p	2445	_	8	100	102	102	103	104	101	102	104	107	105	106

(c)

#### UNCLASSIFIED

#### REFERENCES

- 1. Arthur D. Little, Inc., SQUARE DEAL Exercise Plan, May 1973. (CONFIDENTIAL)
- 2. Maury Center, "SQUARE DEAL Data Analysis Plan," Vol. 1, Maury Center Plan MC-002, January 1974, revised August 1974. (SECRET)
- 3. Maury Center, "SQUARE DEAL Data Analysis Plan," Vol.II, Maury Center Plan MC-002, January 1974. (CONFIDENTIAL)
- 4. Maury Center, "SQUARE DEAL Synopsis Report," Maury Center Report 0015, February 1974. (SECRET)
- 5. M. S. Weinstein and G. E. Ellis, "Final Report on Investigation Conducted under the Diagnostic Plan for Church Anchor and SQUARE DEAL Shot Data," USI, April 1975. (CONFIDENTIAL)
- 6. J. Cybulski and C. Andriani, "CW Propagation Loss for SQUARE DEAL,"
  Naval Research Laboratory, Washington, D.C.
- 7. Naval Oceanographic Office, "Sound Velocity Structure of the Northeast Atlantic Ocean in Summer 1973 During the Square Deal Exercise" (U), Washington, D.C.
- 8. Wood's Hole Oceanographic Institute, "Ambient Noise Report SQUARE DEAL," Woods Hole, Massachusetts.
- 9. V. A. Brunson and H. S. Aurand, Jr., "Horizontal Directivity of Low Frequency Ambient Sea Noise in North Atlantic" (U), NUC, TP-470, Naval Undersea Center, San Diego, California, July 1975. (CONFIDENTIAL)
- 10. "SQUARE DEAL Modeling Evaluation Report", AESD Technical Note 75-C5, October 1975. (CONFIDENTIAL)
- 11. F. H. Lindrop. The Ocean Acoustics of the Rockall Trough; Exercise SQUARE DEAL," Admiralty Research Laboratories, Teddington, England, July 1975.
- 12. Xonics, Inc. "SQUARE DEAL Environmental Acoustics Summary", (CONFIDENTIAL)
- 13. Underwater Systems, Inc., "SUS Source Level Committee Report," Maury Center Report MC-112, November 1975.
- 14. W. E. Wallace, M. S. Weinstein, A. F. Wittenborn, "Report of SUS Source Level Workshop", ARL Conference Center, 7-8 July 1976, Underwater Systems, Inc., Silver Spring, Maryland, 26 July 1976. (Preliminary)

וג ו

UNCLASSIFIED

#### UNCLASSIFIED

- 15. J. B. Gaspin and V. K. Shuler, "Source Levels of Shallow Underwater Explosions," Naval Surface Weapons Center, White Oak Laboratory, Silver Spring, Maryland, NOLTR-71-160, 13 October 1976.
- 16. J. S. Hanna and B. E. Parkins, "Some Considerations in Choosing an Explosive Source and Processing Filter for the Measurement of Transmission Loss," J. Acoust. Soc. Am. <u>56</u>, 378 (1974).

132

UNCLASSIFIED

19 July 1976

DISTRIBUTION LIST FOR ARI-TR-76-37 UNDER CONTRACT NOO014-75-C-0429 CONFIDENTIAL - GDS, 1981

Copy No.	
1	Assistant Director of the Navy (RE&S) Washington, DC 20301 Attn: G. A. Cann
2 3 4 5 6 7 8	Chief of Naval Operations Department of the Navy Washington, DC 20350 Attn: OP-095 OP-951 OP-955 OP-094 OP-096 OP-02 OP-03
9	Chief of Naval Development Headquarters, Naval Material Command Washington, DC 20360 Attn: MAT-035
10 - 11	Commander Naval Air Development Center Warminster, PA 18974
12	Commander in Chief U.S. Atlantic Fleet Norfolk, VA 23511
13 - 14	Commander Oceanographic Systems, Atlantic Box 100 Norfolk, VA 23511
15 16	Chief of Naval Research Department of the Navy Arlington, VA 22217 Attn: Chief Dr. J. B. Hersey

Copy No.	
17	Commanding Officer Naval Research Laboratory Washington, DC 20375 Attn: Commanding Officer
18 19	Code 8100 Code 8160
20	Code 2627
21	Oceanographer of the Navy
	Hoffman Building II
	200 Stovall Street
•	Alexandria, VA 22332 Attn: CDR E. T. Young
	Actin: Clar E. 1. foung
22	Commander
	Naval Air Systems Command
	Department of the Navy Washington, DC 20360
	Attn: Code PMA-264
	Commander
	Naval Electronic Systems Command
	Department of the Navy
	Washington, DC 20360
23 - 26 27	Attn: PME-124, 124/30, 124/40, 124/60
<b>2</b> 8	ELEX-320 RLEX-035
	max-0))
	Commander
	Naval Sea Systems Command
	Department of the Navy Washington, DC 20362
29	Attn: Commander
30	SEA-06H1
31	Strategic Systems Project Office
	Department of the Navy
	Washington, DC 20560
	Attn: PM-1
32 - 33	Antisubmarine Warfare Systems Project Office
	Department of the Navy
	Washington, DC 20360 Attn: PM-4
	esous. Att-T
34	Commanding Officer
	Fleet Numerical Weather Central
	Monterey, CA 93940
	134

Copy No.	
	Commander
	Naval Ocean Systems Center
	San Diego, CA 92132
35 37	Attn: Commander
36 <b>-</b> 37	M. R. Akers
38 39	Dr. R. A. Wagstaff Dr. E. B. Tunstall
40	Dr. R. R. Gardner
,,	
41	Commander
	Naval Surface Weapons Center
	White Oak Laboratory
	Silver Spring, MD 20910
	Commander
	New London Laboratory
	Naval Underwater Systems Center
42	New London, CT 06320
43	Attn: Commander R. L. Martin
•	It, It, Man Oass
	Commander
	Naval Oceanographic Office
	Department of the Navy
1414	Washington, DC 20373 Attn: Commander
45	J. L. Kerling
1.0	•
46	Commanding Officer
	Naval Intelligence Support Center 4301 Suitland Rd.
	Was hington, DC 20390
	Har languous to Logge
	Director for Naval Matters
	Cente for Naval Analysis
1, 49	Anlington, VA 22209
47 48	Attn: Director C. E. Woods
40	
	Commanding Officer
	Naval Ocean Research and Development Activity
49	NSTL Station, MS 39529 Attn: Commanding Officer
50	Code 110
ร์เ	Code 200
52	Code 300
53	Code 320
54	Code 340
51 52 53 54 55 56	Code 400
	Code 500
57 - 59	Code 600 135
	* * *

Copy No.	
60 - 61	NORDA Liaison Office Office of Naval Research Arlington, VA 22217 Attn: K. W. Lackie
62	Defense Advanced Research Projects Agency 1400 Wilson Boulevard Arlington, VA 22209 Attn: CAPT H. Cox
63	ARPA Research Center Unit 1, Bldg. 301A NAS Moffett Field, CA 94035 Attn: E. L. Smith
64	Superintendent Naval Postgraduate School Monterey, CA 93940
65	Commanding Officer and Director Defense Documentation Center Defense Services Administration Cameron Station, Building 5 5010 Duke Street Alexandria, VA 22514
66	Analysis & Technology, Inc. Technology Park, P.O. Box 220 North Stonington, CT 06359 Attn: S. Elam
67	Applied Physics Laboratory The Johns Hopkins University Johns Hopkins Road Laurel, MD 20810 Attn: Dr. G. L. Smith
68	Aprilied Physics Laboratory The University of Washington 1013 NE Fortieth Street Seattle, WA 98195
69 <b>7</b> 0	Arthur D. Little, Inc. Acorn Park Cambridge, MA 02140 Attn: W. G. Sykes

ору	No.	
	71	Bolt, Beranek, and Newman, Inc. 1701 N. Fort Myer Drive Arlington, VA 22209
	72	Bell Telephone Laboratories 2 Whippany Road Whippany, NJ 07981
	73	B-K Dynamics, Inc. 15825 Shady Grove Road Rockville, MD 20850 Attn: P. C. Bernard
	7 <sup>1</sup> +	Daniel Analytical Services Corp. 16821 Buccaneer Lane, Suite 202 Houston, TX 77058
	75	Daniel H. Wagner Associates, Inc. Station Square One Paoli, PA 19301
	76	Daubin Systems Corporation 104 Crandon Blvd. Key Biscayne, FL 33249
	77	General Electric Corporation P.O. Box 4840 Syracuse, NY 13221 Attn: K. D. Greenhalgh
	78	General Electric Corporation RESD 3198 Chestnut Street P.O. Box 7722 Philadelphia, PA 19101 Attn: O. Klima
	79	Lockheed Missiles and Space Company, Inc. P.O. Box 504 Sunnyvale, CA 94088 Attn: R. C. Parsons
	80	Security Office Q-017 University of California - San Diego La Jolla, CA 92093 Attn: V. C. Anderson Scripps Inst. of Oceanography

137

#### Copy No.

81 ORI, Inc. 1400 Spring Street Silver Spring, MD 20910 Attn: Dr. J. I. Bowen

82 Planning Systems, Inc. 7900 Westpark Drive McLean, VA 22101 Attn: Dr. L. P. Solomon

Raythecn Company 83 Submarine Signal Division P.O. Box 360 Portsmouth, RI 02871 Attn: Dr. B. A. Becken

84 Science Applications, Inc. 8400 Westpark Drive McLean, VA 22101 Attn: Dr. J. S. Hanna

85 Summit Research Corporation 1 West Deer Park Drive Gaithersburg, MD 20760

86 Sutron Corporation Suite 700 1925 N. Lynn Street Arlington, VA 22209 Attn: C. H. Dabney

87 Tetra-Tech, Inc. 1911 N. Ft. Meyer Drive Arlington, VA 22209 Attn: W. E. Sims

88 Texas Instruments, Inc. P.O. Box 5474 Dallas, TX 75222 Attn: A. Kirst, Jr.

Tracor, Inc. 89 1601 Research Blvd. Rockville, MD 20850 Attn: J. T. Gottwald

Copy No.	
	TRW, Inc. TRW Defense & Space Systems Group Washington Operation 7600 Colshire Drive McLean, VA 22101
96 91	Attn: R. T. Brown I. B. Gereben
9 <b>2</b>	Undersea Research Corporation 7777 Leesburg Pike, Suite 306 Falls Church, VA 22043 Attn: V. F. Anderson
93	Underwater Systems, Inc. World Building 8121 Georgia Avenue Silver Spring, MD 20910 Attn: Dr. M. S. Weinstein
94	Western Electric Company P.O. Box 20046 Greensboro, NC 27420
95	Woods Hole Oceanographic Institution Woods Hole, MA 02543 Attn: E. E. Hays
96	Xonics, Inc. 6849 Hayvenhurst Avenue Van Nuys, CA 91406 Attn: S. Kulek
97	Glen E. Ellis, ARL:UT
98	Loyd D. Hampton, ARL:UT
99	Kenneth E. Hawker, ARL:UT
100	Stephen K. Mitchell, ARL:UT
101	Jack A. Shooter, ARL:UT
102	Ruben H. Wallace, ARL:UT
103	Steven L. Watkins, ARL:UT
10%	Library, ARL:UT
.05 - 11.6	Reserve, ARL:UT
	(The reverse of this page is blank.)  CONFIDENTIAL



#### **DEPARTMENT OF THE NAVY**

OFFICE OF NAVAL RESEARCH 875 NORTH RANDOLPH STREET **SUITE 1425 ARLINGTON VA 22203-1995** 

IN REPLY REFER TO:

5510/1 Ser 321OA/011/06 31 Jan 06

#### MEMORANDUM FOR DISTRIBUTION LIST

Subj: DECLASSIFICATION OF LONG RANGE ACOUSTIC PROPAGATION PROJECT (LRAPP) DOCUMENTS

Ref:

(a) SECNAVINST 5510.36

Encl: (1) List of DECLASSIFIED LRAPP Documents

- 1. In accordance with reference (a), a declassification review has been conducted on a number of classified LRAPP documents.
- 2. The LRAPP documents listed in enclosure (1) have been downgraded to UNCLASSIFIED and have been approved for public release. These documents should be remarked as follows:

Classification changed to UNCLASSIFIED by authority of the Chief of Naval Operations (N772) letter N772A/6U875630, 20 January 2006.

DISTRIBUTION STATEMENT A: Approved for Public Release; Distribution is unlimited.

3. Questions may be directed to the undersigned on (703) 696-4619, DSN 426-4619.

**BRIAN LINK** 

By direction

## Subj: DECLASSIFICATION OF LONG RANGE ACOUSTIC PROPAGATION PROJECT (LRAPP) DOCUMENTS

#### **DISTRIBUTION LIST:**

NAVOCEANO (Code N121LC - Jaime Ratliff)

NRL Washington (Code 5596.3 – Mary Templeman)

PEO LMW Det San Diego (PMS 181)

DTIC-OCQ (Larry Downing)

ARL, U of Texas

Blue Sea Corporation (Dr.Roy Gaul)

ONR 32B (CAPT Paul Stewart)

ONR 321OA (Dr. Ellen Livingston)

APL, U of Washington

APL, Johns Hopkins University

ARL, Penn State University

MPL of Scripps Institution of Oceanography

WHOI

**NAVSEA** 

**NAVAIR** 

**NUWC** 

**SAIC** 

# **Declassified LRAPP Documents**

			Publication Source	Pirh	Current	
Report Number	Fersonal Author	Title	(Originator)	Date	Availability	Class.
ARLTR7952	Focke, K. C., et al.	CHURCH STROKE 2 CRUISE 5 PAR/ACODAC ENVIRONMENTAL ACOUSTIC MEASUREMENTS AND ANALYSIS (U)	University of Texas, Applied Research Laboratories	791029	ADC025102; NS; AU; ND	C
Unavailable	Van Wyckhouse, R. J.	SYNBAPS. VOLUME I. DATA BASE SOURCES AND DATA PREPARATION	Naval Ocean R&D Activity	791201	ADC025193	C
NORDATN63	Brunson, B. A., et al.	ENVIRONMENTAL EFFECTS ON LOW FREQUENCY TRANSMISSION LOSS IN THE GULF OF MEXICO (U)	Naval Ocean R&D Activity	800901	ADC029543; ND	C
NORDATN80C	Gereben, I. B.	ACOUSTIC SIGNAL CHARACTERISTICS MEASURED WITH THE LAMBDA III DURING CHURCH STROKE III (U)	Naval Ocean R&D Activity	800915	ADC023527; NS; AU; ND	C
NOSCTR664	Gordon, D. F.	ARRAY SIMULATION AT THE BEARING STAKE SITES	Naval Ocean Systems Center	810401	ADC025992; NS; AU: ND	C
NOSCTR703	Gordon, D. F.	NORMAL MODE ANALYSIS OF PROPAGATION LOSS AT THE BEARING STAKE SITES (U)	Naval Ocean Systems Center	810801	ADC026872; NS; AU; ND	C
NOSCTR680	Neubert, J. A.	COHERENCE VARIABILITY OF ARRAYS DURING BEARING STAKE (U)	Naval Ocean Systems Center	810801	ADC028075; NS; ND	C
HSECO735	Luehrmann, W. H.	SQUARE DEAL R/V SEISMIC EXPLORER FIELD OPERATIONS REPORT (U)	Seismic Engineering Co.	731121	AD0530744; NS; ND	C; U
MPL-C-42/76	Morris, G. B.	CHURCH ANCHOR EXPLOSIVE SOURCE (SUS) PROPAGATION MEASUREMENTS FROM R/P FLIP (U)	Marine Physical Laboratory	760701	ADC010072; AU; ND	C; U
ARLTR7637	Mitchell, S. K., et al.	SQUARE DEAL EXPLOSIVE SOURCE (SUS) PROPAGATION MEASUREMENTS. (U)	University of Texas, Applied Research Laboratories	760719	ADC014196; NS; AU; ND	c; u
NORDAR23	Fenner, D. F.	SOUND SPEED STRUCTURE OF THE NORTHEAST ATLANTIC OCEAN IN SUMMER 1973 DURING THE	Naval Ocean R&D Activity	800301	ADC029546; NS; ND	C; U
NOOTR230	Bucca, P. J.	CH	Naval Oceanographic Office	751201	NS; AU; ND	C;U
ONR SP 2-69; MC PLAN-01	Unavailable	PARKA II EXPERIMENT UTILIZING SEA SPIDER, ONR SCIENTIFIC PLAN 2-69 (U)	Maury Center for Ocean Science	690626	ADB020846; ND	n
Unavailable	Unavailable		Maury Center for Ocean Science	691101	AD0506209	n
USRD CR 3105	Unavailable	SEA SPIDER TRANSPONDER TRANSDUCER	search Lat	700505	QN	 U
MC PLAN 05; ONR Scientific Plan 1-71	Unavailable	(t	Maury Center for Ocean Science	701020	ND	n
ACR-170 VOL.1	Hurdle, B. G.		Naval Research Laboratory	701118	QN	Ω
MC-003-VOL-2	Unavailable	THE PARKA I EXPERIMENT. APPENDICES- PACIFIC ACOUSTIC RESEARCH KANEOHE-ALASKA (U)	Maury Center for Ocean Science	710101	ND	U

ENCL (1)